

RECEIVED

AUG 26 2015

DEPARTMENT OF ENVIRONMENTAL QUALITY
STATE A Q PROGRAM



TransCanada
201 W. North River Drive., Suite 505
Spokane, WA 99201

tel 832.320.5127
fax 832.320.6127
email lionel_philip@TransCanada.com

Air Quality Program Office – Application Processing
Department of Environmental Quality
1410 N. Hilton
Boise, ID 83706-1255

RE: Submittal of Permit Renewal Applications for Tier I Permit Numbers T1-2010.0100 and T1-2010.0099

Dear Sir/madam:

TransCanada is please to submit the applications to renew two of our Tier 1 Permits. Specifically, we are submitting applications for Permit Numbers T1-2010.0099 for our Compressor Station located near Eastport, ID; and T1-2010.0100 for our compressor Station located near Samuels, ID. Attached are the marked-up permits with the proposed changes and comments.

Attached please find the following:

1. Form CSTI for T1-2010.0099 and T1-2010.0100
2. Form GI for both T1-2010.0099 and T1-2010.0100
3. Regulation Review and Applicability Form FRA for both T1-2010.0099 and T1-2010.0100 with Applicability Analysis
4. Marked-up Tier I Operating Permits with TransCanada's proposed changes and comments for both T1-2010.0099 and T1-2010.0100

Should you have any questions regarding these applications, please do not hesitate to contact me at 832-320-5127 or email at lionel_philip@TransCanada.com.

Sincerely,

Lionel J. Philip
Air Quality Specialist

cc

Environmental files,
Station 3 Air Files



DEQ AIR QUALITY PROGRAM
1410 N. Hilton, Boise, ID 83706
For assistance, call the
Air Permit Hotline – 1-877-5PERMIT

Cover Sheet for Air Permit Application – Tier I **Form CSTI**

Revision 5
08/28/08

Please see instructions on page 2 before filling out the form.

COMPANY NAME, FACILITY NAME, AND FACILITY ID NUMBER			
1. Company Name	TransCanada, Gas Transmission Northwest		
2. Facility Name	Compressor Station 3	3. Facility ID No.	021-00013
4. Brief Project Description - One sentence or less	Renewal of Tier 1 Permit Number T1-2010.0099		
PERMIT APPLICATION TYPE			
5. <input type="checkbox"/> Initial Tier I <input type="checkbox"/> Tier I Administrative Amendment <input type="checkbox"/> Tier I Minor Modification <input type="checkbox"/> Tier I Significant Modification			
<input checked="" type="checkbox"/> Tier I Renewal: Permit No.: T1-2010.0099 Date Issued: March 7, 2011			
FORMS INCLUDED			
Include d	N/A	Forms	DEQ Verify
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Form CSTI – Cover Sheet	<input type="checkbox"/>
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Form GI – Facility Information	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form EU0 – Emissions Units General	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form EU1– Industrial Engine Information Please specify number of EU1s attached: _____	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form EU2– Nonmetallic Mineral Processing Plants Please specify number of EU2s attached: _____	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form EU3– Spray Paint Booth Information Please specify number of EU3s attached: _____	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form EU4– Cooling Tower Information Please specify number of EU4s attached: _____	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form EU5 – Boiler Information Please specify number of EU5s attached: _____	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form CBP– Concrete Batch Plant Please Specify number of CBPs attached: _____	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form HMAP – Hot Mix Asphalt Plant Please specify number of HMAPs attached: _____	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	PERF – Portable Equipment Relocation Form	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form BCE– Baghouses Control Equipment	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form SCE– Scrubbers Control Equipment	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form VSCE – Venturi Scrubber Control Equipment	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form ESP – Electrostatic Precipitator	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form AO – Afterburner/Oxidizer	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form CYS – Cyclone Separator	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form CA – Carbon Adsorber	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Forms EI-CP1 - EI-CP4– Emissions Inventory– criteria pollutants (Excel workbook, all 4 worksheets)	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Form CAM – Compliance Assurance Monitoring	<input type="checkbox"/>
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Form FRA – Federal Regulation Applicability	<input type="checkbox"/>

Instructions for Form CSTI

This form is the cover sheet for an air quality permit application. It provides DEQ with basic information regarding the company and the proposed permitting action. This form helps DEQ efficiently determine whether the application is administratively complete. This form also provides the applicant with a list of forms available to aid the applicant to successfully submit a complete application.

Company Name, Facility Name, and Facility ID Number

- 1-3. Provide the name of your company, the name of the facility (if different than company name), and the facility identification (ID) number (Facility ID No.) in the boxes provided. The facility ID number is also known as the AIRS number or AIRS/AFS number (example: 095-00077). If you already have a permit, the facility ID number is located in the upper right hand corner of the cover page. The facility ID number must be provided unless your facility has not received one, in which case you may leave this box empty. **Use these same names and ID number on all forms.** This is useful in case any pages of the application are separated.
4. Provide a brief description of this permitting project in one sentence or less. Examples might be "Tier I Administrative Amendment to allow for the change of ownership of this facility" or "Tier I Significant Modification to change the existing monitoring, recordkeeping, and reporting requirements Boiler #1." **This description will be used by DEQ as a unique identifier for this permitting project, in conjunction with the name(s) and ID number referenced in 1-3.** You will need to put this description, using the exact same words, on all other forms that are part of this project application. This is useful in case any pages of the application are separated.

If this Tier I is being issued as a result of a PTC issued pursuant to IDAPA 58.01.01.209.05.c, the source or modification may operate upon submittal for an administrative amendment issued pursuant to IDAPA 58.01.01.381.

Permit Application Type

5. Provide the reason you are submitting the permit application by checking the appropriate box and filling in the number and/or date if needed.

Forms Included

Check the "Included" box for each form included in this permit to construct application. If there are multiples of a form for multiple units of that type, check the box and fill in the number of forms in the blank provided.

The "N/A" box should only be checked if the form is absolutely unnecessary to complete the application. Additional information may be requested.

When complete, enclose the hardcopy application certified by a responsible official (as defined in IDAPA 58.01.01.006.94), and send to:

Air Quality Program Office – Application Processing
Department of Environmental Quality
1410 N. Hilton
Boise, ID 83706-1255

**DEQ AIR QUALITY PROGRAM**

1410 N. Hilton, Boise, ID 83706

For assistance, call the

Air Permit Hotline: 1-877-5PERMIT

General Information **Form GI**

Revision 7

6/29/12

Please see instructions on back page before filling out the form. All information is required. If information is missing, the application will not be processed.

Identification

1. Facility name

Compressor Station 3

2. Existing facility identification number

021-00013

☐ Check if new facility (not yet operating)

3. Brief project description Renewal of Tier 1 Permit Number T1-2010.0099

Facility Information

4. Primary facility permitting contact name Lionel Philip

Contact type Facility permitting contact

Telephone number 832-320-5127

E-mail lionel_philip@transcanada.com

5. Alternate facility permitting contact name Michael Antes

Alternate contact type Facility permitting contact

Telephone number 509-533-2865

E-mail michael_antes@transcanada.com

6. Mailing address where permit will be sent (street/city/county/state/zip code)

700 Louisiana Street Suite 700, Houston, TX 77002

7. Physical address of permitted facility (if different than mailing address) (street/city/county/state/zip code)

Highway 95, approximately 2.2 miles south of Eastport

8. Is the equipment portable?

☐ Yes*☒ No

*If yes, complete and attach PERF; see instructions.

9. NAICS codes: Primary NAICS 486210

Secondary NAICS

10. Brief business description and principal product produced

Transmission of natural gas via pipeline using compression derived from multiple turbine based sources.

11. Identify any adjacent or contiguous facility this company owns and/or operates

N/A

12. Specify type of application ☐ Permit to construct (PTC); application fee of \$1,000 required. See instructions.☒ Tier I permit☐ Tier II permit☐ Tier II/Permit to construct

For Tier I permitted facilities only: If you are applying for a PTC then you must also specify how the PTC will be incorporated into the Tier I permit.

☐ Co-process Tier I modification and PTC☐ Incorporate PTC at the time of Tier I renewal☐ Administratively amend the Tier I permit to incorporate the PTC upon applicant's request (IDAPA 58.01.01.209.05.a, b, or c)**Certification**

In accordance with IDAPA 58.01.01.123 (Rules for the Control of Air Pollution in Idaho), I certify based on information and belief formed after reasonable inquiry, the statements and information in the document(s) are true, accurate, and complete.

13. Responsible official's name Ken Leier

Official's title

Regional Director, Pipeline Operations and Maintenance

Official's address 201 W North River Dr. #505 Spokane, Washington 99201

Telephone number 503-533-2831 ext. 32831

E-mail ken_leier@transcanada.com

Official's signature

Date

08/17/15

☒ 14. Check here to indicate that you want to review the draft permit before final issuance.

Instructions for Form GI

This form is used by DEQ to identify a company or facility, equipment locations, and personnel involved with the permit application. Additional information may be required.

Identification

1. Provide the facility name. If the facility is *doing business as* (dba) a facility different in name than the primary facility, provide the dba name.
2. If the facility is an existing permitted facility in Idaho, provide the facility identification number. If the facility is new and not yet operating, check the box.
3. Provide a brief project description as on Form CS, Cover Sheet. This is useful in case any pages of the application are separated.

Facility information

4. Provide name of the *primary* person who should be contacted regarding this permit. Provide telephone number and e-mail address for the primary person.
5. Provide name of an *alternate* person who should be contacted if the person listed in 4 is not available. Provide telephone number and e-mail address for the alternate person.
6. Provide the mailing address where DEQ should mail the permit.
7. Provide the physical address where the equipment is located (if different than 6).
8. Indicate if the permitted equipment is portable by checking the appropriate box. If the permitted equipment is portable, complete and attach the Portable Equipment Relocation Form (PERF) to this application. The PERF is available from DEQ's website at http://www.deq.idaho.gov/media/576773-ptc_relocation.pdf or http://www.deq.idaho.gov/media/576769-ptc_relocation.doc (for Word format).
9. Provide the North American Industry Classification System (NAICS) code for your facility. NAICS codes can be found at <http://www.census.gov/epcd/naics02/naicod02.htm>.
10. Describe the primary activity and principal product of your business as it relates to the NAICS code listed in 9.
11. Identify and describe any other sources or equipment owned and operated by the primary facility that are located on contiguous or adjacent properties and the role the source or equipment plays in supporting the primary facility.
12. Check the box describing the type of permit application.

Important note: If application is for a permit to construct (PTC), include the application fee of \$1,000 when submitting the application. Per IDAPA 58.01.01.226.02, DEQ cannot process the application without the fee, which must be submitted with the application.

For existing Tier I facilities that are applying for a PTC, the applicant must specify how the PTC will be incorporated into the Tier I permit (IDAPA 58.01.01.209.05). If you have questions, call the Air Permit Hotline at 1-877-573-7648.

Certification

13. Provide the name, title, address, telephone number, and e-mail of the facility's responsible official. Responsible official is defined in IDAPA 58.01.01.006.99. The responsible official must sign and date the application before it is submitted to DEQ.
14. Check this box to indicate that you want to review a draft before the final permit is issued.



DEQ AIR QUALITY PROGRAM
 1410 N. Hilton, Boise, ID 83706
 For assistance, call the
Air Permit Hotline – 1-877-5PERMIT

AIR PERMIT APPLICATION

Revision 6
 10/7/09

For each box in the table below, CTRL+click on the blue underlined text for instructions and information.

IDENTIFICATION	
1. Company Name: TransCanada, Gas Transmission Northwest	2. Facility Name: Compressor Station 3
3. Brief Project Description: Renewal of Tier 1 Permit Number T1-2010.0099	
APPLICABILITY DETERMINATION	
4. List applicable subparts of the New Source Performance Standards (NSPS) (40 CFR part 60). Examples of NSPS affected emissions units include internal combustion engines, boilers, turbines, etc. The applicant must thoroughly review the list of affected emissions units.	List of applicable subpart(s): GG KKKK <input type="checkbox"/> Not Applicable
5. List applicable subpart(s) of the National Emission Standards for Hazardous Air Pollutants (NESHAP) found in 40 CFR part 61 and 40 CFR part 63 . Examples of affected emission units include solvent cleaning operations, industrial cooling towers, paint stripping and miscellaneous surface coating. EPA has a web page dedicated to NESHAP that should be useful to applicants.	List of applicable subpart(s): ZZZZ <input type="checkbox"/> Not Applicable
6. For each subpart identified above, conduct a complete a regulatory analysis using the instructions and referencing the example provided on the following pages. Note - Regulatory reviews must be submitted with sufficient detail so that DEQ can verify applicability and document in legal terms why the regulation applies. Regulatory reviews that are submitted with insufficient detail will be determined incomplete.	<input checked="" type="checkbox"/> A detailed regulatory review is provided (Follow instructions and example). <input type="checkbox"/> DEQ has already been provided a detailed regulatory review. Give a reference to the document including the date.
<p align="center">IF YOU ARE UNSURE HOW TO ANSWER ANY OF THESE QUESTIONS, CALL THE AIR PERMIT HOTLINE AT 1-877-5PERMIT</p> <p><i>It is emphasized that it is the applicant's responsibility to satisfy all technical and regulatory requirements, and that DEQ will help the applicant understand what those requirements are <u>prior</u> to the application being submitted but that DEQ will not perform the required technical or regulatory analysis on the applicant's behalf.</i></p>	

Instructions for Form FRA

Item 4 & 5. It is important that facilities review the most recent federal regulations when submitting their permit application to DEQ. Current federal regulations can be found at the following Web site: http://ecfr.gpoaccess.gov/cgi/t/text/text-idx?&c=ecfr&tpl=/ecfrbrowse/Title40/40tab_02.tpl.

Item 6. For each applicable subpart identified under items 4-5 conduct a complete regulatory analysis. The facility must follow the procedure given below or obtain permission from DEQ to provide the necessary information using an alternative procedure:

1. Retrieve a TEXT or PDF copy of the applicable federal regulation subpart(s) online at <http://www.gpoaccess.gov/cfr/retrieve.html>
2. Copy and paste the regulation(s) into your DEQ air permit application.
3. Highlight or underline sections in the regulation(s) that are applicable to the source(s).
4. Under each section of the subpart, explain why the source is subject to the section, or why the source is not subject to the section. When providing the explanation use a different font than the regulation (i.e. ***bold, italic***) so that it is easy for the reader to determine the text that the applicant has provided. An example NSPS regulatory analysis is attached. The applicant must provide all necessary information needed to determine applicability. If information is lacking or the analysis is incomplete the application will be determined incomplete.

EPA provides a web site dedicated to NSPS/NESHAP applicability determinations that may be useful to applicants. Follow this link to the applicability determination index [Clean Air Act Applicability Determination Index - Compliance Monitoring - EPA](#). Another useful source of information is the preamble to the regulation which is published in the Federal Register on the date the regulation was promulgated. Federal Registers may be found online at [Federal Register: Main Page](#). The date the regulation was published in the Federal Register is included in the footnotes of the regulation.

5. DEQ will assist in identifying the applicable requirements that the applicant must include in the application but will not perform the required technical or regulatory analysis on the applicant's behalf. Applicants should contact the Air Quality Permit Hotline (1-877-573-7648) to discuss NSPS/NESHAP regulatory analysis requirements or to schedule a meeting.
6. It also benefits facilities to document a non-applicability determination on federal air regulations which appear to apply to the facility but actually do not. A non-applicability determination will avoid future confusion and expedite the air permit application review. If you conduct an applicability determination and find that your activity is not NSPS or NESHAP affected facility an analysis should be submitted using the methods described above.
7. **It is not sufficient to simply provide a copy of the NSPS or NESHAP. The applicant must address each section of the regulation as described above and as shown in the example that is provided.**

GTN Compressor Station 3 and 4 – Applicability Analysis

Title 40: Protection of Environment

PART 63—NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR SOURCE CATEGORIES (CONTINUED)

Browse Next

Subpart ZZZZ—National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

Source: 69 FR 33506, June 15, 2004, unless otherwise noted.

What This Subpart Covers

§ 63.6580 What is the purpose of subpart ZZZZ?

Subpart ZZZZ establishes national emission limitations and operating limitations for hazardous air pollutants (HAP) emitted from stationary reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions. This subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations and operating limitations.

Compressor Station 4 and Station 3 but has one spark ignition stationary reciprocating internal combustion engine. See below for discussion of applicability.

[73 FR 3603, Jan. 18, 2008]

§ 63.6585 Am I subject to this subpart?

You are subject to this subpart if you own or operate a stationary RICE at a major or area source of HAP emissions, except if the stationary RICE is being tested at a stationary RICE test cell/stand.

The Compressor Station is not a major source for HAP emissions.

(a) A stationary RICE is any internal combustion engine which uses reciprocating motion to convert heat energy into mechanical work and which is not mobile. Stationary RICE differ from mobile RICE in that a stationary RICE is not a non-road engine as defined at 40 CFR 1068.30, and is not used to propel a motor vehicle or a vehicle used solely for competition.

The engine is stationary RICE.

(b) A major source of HAP emissions is a plant site that emits or has the potential to emit any single HAP at a rate of 10 tons (9.07 megagrams) or more per year

or any combination of HAP at a rate of 25 tons (22.68 megagrams) or more per year, except that for oil and gas production facilities, a major source of HAP emissions is determined for each surface site.

Station 4 and Station 3 are not a major source of HAP emissions.

(c) An area source of HAP emissions is a source that is not a major source.

The Compressor Station is an area source of HAP emissions.

(d) If you are an owner or operator of an area source subject to this subpart, your status as an entity subject to a standard or other requirements under this subpart does not subject you to the obligation to obtain a permit under 40 CFR part 70 or 71, provided you are not required to obtain a permit under 40 CFR 70.3(a) or 40 CFR 71.3(a) for a reason other than your status as an area source under this subpart. Notwithstanding the previous sentence, you must continue to comply with the provisions of this subpart as applicable.

Station 4 and Station 3 has a Title V permit.

(e) If you are an owner or operator of a stationary RICE used for national security purposes, you may be eligible to request an exemption from the requirements of this subpart as described in 40 CFR part 1068, subpart C.

The RICE is not used for national security purposes

[69 FR 33506, June 15, 2004, as amended at 73 FR 3603, Jan. 18, 2008]

§ 63.6590 What parts of my plant does this subpart cover?

[Link to an amendment published at 75 FR 51588, Aug. 20, 2010.](#)

This subpart applies to each affected source.

(a) *Affected source.* An affected source is any existing, new, or reconstructed stationary RICE located at a major or area source of HAP emissions, excluding stationary RICE being tested at a stationary RICE test cell/stand.

The RICE is not an affected source, it is an existing source, see below.

(1) *Existing stationary RICE.*

The RICE is an existing source.

(i) For stationary RICE with a site rating of more than 500 brake horsepower (HP) located at a major source of HAP emissions, a stationary RICE is existing if you

commenced construction or reconstruction of the stationary RICE before December 19, 2002.

The RICE is greater than 500 brake horsepower, but is not located at a major source of HAP emissions.

(ii) For stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.

The RICE is greater than 500 brake horsepower and is not located at a major source of HAP emissions.

(iii) For stationary RICE located at an area source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.

The RICE was constructed before June 12, 2006. It has not been reconstructed since that date

(iv) A change in ownership of an existing stationary RICE does not make that stationary RICE a new or reconstructed stationary RICE.

A change of ownership is not being sought with this renewal application.

(2) *New stationary RICE.*

The RICE is not a new source, see below for discussion.

(i) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions is new if you commenced construction of the stationary RICE on or after December 19, 2002.

The RICE is not a new source, it is not located at a major source of HAP emissions, and construction was commenced before December 19, 2002.

(ii) A stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions is new if you commenced construction of the stationary RICE on or after June 12, 2006.

The RICE is greater than 500 hp.

(iii) A stationary RICE located at an area source of HAP emissions is new if you commenced construction of the stationary RICE on or after June 12, 2006.

The RICE is not new, it commenced construction after June 12, 2006.

(3) *Reconstructed stationary RICE.*

The RICE is not a reconstructed source, see below for discussion.

(i) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions is reconstructed if you meet the definition of reconstruction in §63.2 and reconstruction is commenced on or after December 19, 2002.

The RICE is not a reconstructed source, it is not located at a major source of HAP emissions, and reconstruction was commenced before December 19, 2002.

(ii) A stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions is reconstructed if you meet the definition of reconstruction in §63.2 and reconstruction is commenced on or after June 12, 2006.

The RICE is greater than 500 hp.

(iii) A stationary RICE located at an area source of HAP emissions is reconstructed if you meet the definition of reconstruction in §63.2 and reconstruction is commenced on or after June 12, 2006.

The RICE is not reconstructed, it was constructed after June 12, 2006.

(b) *Stationary RICE subject to limited requirements.* (1) An affected source which meets either of the criteria in paragraphs (b)(1)(i) through (ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).

The RICE is not subject to limited requirements, see discussion below

(i) The stationary RICE is a new or reconstructed emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions.

The RICE is not new or reconstructed and is not located in a major source of HAP emissions. The RICE meets the definition of "emergency" see applicable section below.

(ii) The stationary RICE is a new or reconstructed limited use stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions.

The RICE is not new or reconstructed and is not located in a major source of HAP emissions.

(2) A new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis must meet the initial notification requirements of §63.6645(h) and the requirements of §§63.6625(c), 63.6650(g), and 63.6655(c). These stationary RICE do not have to meet the emission limitations and operating limitations of this subpart.

The RICE does not combust landfill or digester gas.

(3) A stationary RICE which is an existing spark ignition 4 stroke rich burn (4SRB) stationary RICE located at an area source of HAP emissions; an existing spark ignition 4SRB stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions; an existing spark ignition 2 stroke lean burn (2SLB) stationary RICE; an existing spark ignition 4 stroke lean burn (4SLB) stationary RICE; an existing compression ignition emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions; an existing spark ignition emergency or limited use stationary RICE; an existing limited use stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions; an existing stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis; or an existing stationary residential, commercial, or institutional emergency stationary RICE located at an area source of HAP emissions, does not have to meet the requirements of this subpart and of subpart A of this part. No initial notification is necessary.

The RICE is an existing spark ignition use engine and does have to meet recordkeeping requirements of Subpart ZZZZ and Subpart A of the part.

(c) *Stationary RICE subject to Regulations under 40 CFR Part 60.* An affected source that is a new or reconstructed stationary RICE located at an area source, or is a new or reconstructed stationary RICE located at a major source of HAP emissions and is a spark ignition 2 stroke lean burn (2SLB) stationary RICE with a site rating of less than 500 brake HP, a spark ignition 4 stroke lean burn (4SLB) stationary RICE with a site rating of less than 250 brake HP, or a 4 stroke rich burn (4SRB) stationary RICE with a site rating of less than or equal to 500 brake HP, a stationary RICE with a site rating of less than or equal to 500 brake HP which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, an emergency or limited use stationary RICE with a site rating of less than or equal to 500 brake HP, or a compression ignition (CI) stationary RICE with a site rating of less than or equal to 500 brake HP, must meet the requirements of this part by meeting the requirements of 40

CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines. No further requirements apply for such engines under this part.

The RICE is not an “affected source”, see above.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3604, Jan. 18, 2008; 75 FR 9674, Mar. 3, 2010; 75 FR 37733, June 30, 2010]

§ 63.6595 When do I have to comply with this subpart?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

[Link to an amendment published at 75 FR 51589, Aug. 20, 2010.](#)

(a) *Affected Sources.* (1) If you have an existing stationary RICE, excluding existing non-emergency CI stationary RICE, with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than June 15, 2007. If you have an existing non-emergency CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, an existing stationary CI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, or an existing stationary CI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than May 3, 2013.

(2) If you start up your new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions before August 16, 2004, you must comply with the applicable emission limitations and operating limitations in this subpart no later than August 16, 2004.

(3) If you start up your new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions after August 16, 2004, you must comply with the applicable emission limitations and operating limitations in this subpart upon startup of your affected source.

(4) If you start up your new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions before January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart no later than January 18, 2008.

(5) If you start up your new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions

after January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart upon startup of your affected source.

(6) If you start up your new or reconstructed stationary RICE located at an area source of HAP emissions before January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart no later than January 18, 2008.

(7) If you start up your new or reconstructed stationary RICE located at an area source of HAP emissions after January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart upon startup of your affected source.

(b) *Area sources that become major sources.* If you have an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP, the compliance dates in paragraphs (b)(1) and (2) of this section apply to you.

(1) Any stationary RICE for which construction or reconstruction is commenced after the date when your area source becomes a major source of HAP must be in compliance with this subpart upon startup of your affected source.

(2) Any stationary RICE for which construction or reconstruction is commenced before your area source becomes a major source of HAP must be in compliance with the provisions of this subpart that are applicable to RICE located at major sources within 3 years after your area source becomes a major source of HAP.

(c) If you own or operate an affected source, you must meet the applicable notification requirements in §63.6645 and in 40 CFR part 63, subpart A.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3604, Jan. 18, 2008; 75 FR 9675, Mar. 3, 2010]

Emission and Operating Limitations

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

§ 63.6600 What emission limitations and operating limitations must I meet if I own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions?

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart.

(a) If you own or operate an existing, new, or reconstructed spark ignition 4SRB stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 1a to this subpart and the operating limitations in Table 1b to this subpart which apply to you.

(b) If you own or operate a new or reconstructed 2SLB stationary RICE with a site rating of more than 500 brake HP located at major source of HAP emissions, a new or reconstructed 4SLB stationary RICE with a site rating of more than 500 brake HP located at major source of HAP emissions, or a new or reconstructed CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 2a to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

(c) If you own or operate any of the following stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the emission limitations in Tables 1a, 2a, 2c, and 2d to this subpart or operating limitations in Tables 1b and 2b to this subpart: an existing 2SLB stationary RICE; an existing 4SLB stationary RICE; a stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis; an emergency stationary RICE; or a limited use stationary RICE.

(d) If you own or operate an existing non-emergency stationary CI RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 2c to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

[73 FR 3605, Jan. 18, 2008, as amended at 75 FR 9675, Mar. 3, 2010]

§ 63.6601 What emission limitations must I meet if I own or operate a 4SLB stationary RICE with a site rating of greater than or equal to 250 brake HP and less than 500 brake HP located at a major source of HAP emissions?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

[Link to an amendment published at 75 FR 51589, Aug. 20, 2010.](#)

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart. If you own or operate a new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at major source of HAP emissions manufactured on or after January 1, 2008, you

must comply with the emission limitations in Table 2a to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

[73 FR 3605, Jan. 18, 2008, as amended at 75 FR 9675, Mar. 3, 2010]

§ 63.6602 What emission limitations must I meet if I own or operate an existing stationary CI RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

[Link to an amendment published at 75 FR 51589, Aug. 20, 2010.](#)

If you own or operate an existing stationary CI RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 2c to this subpart which apply to you. Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart.

[75 FR 9675, Mar. 3, 2010]

§ 63.6603 What emission limitations and operating limitations must I meet if I own or operate an existing stationary CI RICE located at an area source of HAP emissions?

[Link to an amendment published at 75 FR 51589, Aug. 20, 2010.](#)

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart.

(a) If you own or operate an existing stationary CI RICE located at an area source of HAP emissions, you must comply with the requirements in Table 2d to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

(b) If you own or operate an existing stationary non-emergency CI RICE greater than 300 HP located at area sources in areas of Alaska not accessible by the Federal Aid Highway System (FAHS) you do not have to meet the numerical CO emission limitations specified in Table 2d to this subpart. Existing stationary non-emergency CI RICE greater than 300 HP located at area sources in areas of Alaska not accessible by the FAHS must meet the management practices that are shown for stationary non-emergency CI RICE less than or equal to 300 HP in Table 2d to this subpart.

[75 FR 9675, Mar. 3, 2010]

§ 63.6604 What fuel requirements must I meet if I own or operate an existing stationary CI RICE?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

[Link to an amendment published at 75 FR 51589, Aug. 20, 2010.](#)

If you own or operate an existing non-emergency CI stationary RICE with a site rating of more than 300 brake HP with a displacement of less than 30 liters per cylinder that uses diesel fuel, you must use diesel fuel that meets the requirements in 40 CFR 80.510(b) for nonroad diesel fuel. Existing non-emergency CI stationary RICE located in Guam, American Samoa, the Commonwealth of the Northern Mariana Islands, or at area sources in areas of Alaska not accessible by the FAHS are exempt from the requirements of this section.

[75 FR 9675, Mar. 3, 2010]

General Compliance Requirements

§ 63.6605 What are my general requirements for complying with this subpart?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) You must be in compliance with the emission limitations and operating limitations in this subpart that apply to you at all times.

(b) At all times you must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require you to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

[75 FR 9675, Mar. 3, 2010]

Testing and Initial Compliance Requirements

§ 63.6610 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions?

If you own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions you are subject to the requirements of this section.

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) You must conduct the initial performance test or other initial compliance demonstrations in Table 4 to this subpart that apply to you within 180 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions in §63.7(a)(2).

(b) If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004 and own or operate stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must demonstrate initial compliance with either the proposed emission limitations or the promulgated emission limitations no later than February 10, 2005 or no later than 180 days after startup of the source, whichever is later, according to §63.7(a)(2)(ix).

(c) If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004 and own or operate stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, and you chose to comply with the proposed emission limitations when demonstrating initial compliance, you must conduct a second performance test to demonstrate compliance with the promulgated emission limitations by December 13, 2007 or after startup of the source, whichever is later, according to §63.7(a)(2)(ix).

(d) An owner or operator is not required to conduct an initial performance test on units for which a performance test has been previously conducted, but the test must meet all of the conditions described in paragraphs (d)(1) through (5) of this section.

(1) The test must have been conducted using the same methods specified in this subpart, and these methods must have been followed correctly.

(2) The test must not be older than 2 years.

(3) The test must be reviewed and accepted by the Administrator.

(4) Either no process or equipment changes must have been made since the test was performed, or the owner or operator must be able to demonstrate that the

results of the performance test, with or without adjustments, reliably demonstrate compliance despite process or equipment changes.

(5) The test must be conducted at any load condition within plus or minus 10 percent of 100 percent load.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3605, Jan. 18, 2008]

§ 63.6611 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate a 4SLB SI stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions?

[Link to an amendment published at 75 FR 51589, Aug. 20, 2010.](#)

If you own or operate a new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions, you must conduct an initial performance test within 240 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions specified in Table 4 to this subpart, as appropriate.

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

[73 FR 3605, Jan. 18, 2008]

§ 63.6612 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate an existing stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing stationary RICE located at an area source of HAP emissions?

[Link to an amendment published at 75 FR 51589, Aug. 20, 2010.](#)

If you own or operate an existing CI stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing stationary CI RICE located at an area source of HAP emissions you are subject to the requirements of this section.

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) You must conduct any initial performance test or other initial compliance demonstration according to Tables 4 and 5 to this subpart that apply to you within 180 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions in §63.7(a)(2).

(b) An owner or operator is not required to conduct an initial performance test on a unit for which a performance test has been previously conducted, but the test must meet all of the conditions described in paragraphs (b)(1) through (4) of this section.

(1) The test must have been conducted using the same methods specified in this subpart, and these methods must have been followed correctly.

(2) The test must not be older than 2 years.

(3) The test must be reviewed and accepted by the Administrator.

(4) Either no process or equipment changes must have been made since the test was performed, or the owner or operator must be able to demonstrate that the results of the performance test, with or without adjustments, reliably demonstrate compliance despite process or equipment changes.

[75 FR 9676, Mar. 3, 2010]

§ 63.6615 When must I conduct subsequent performance tests?

If you must comply with the emission limitations and operating limitations, you must conduct subsequent performance tests as specified in Table 3 of this subpart.

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

§ 63.6620 What performance tests and other procedures must I use?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) You must conduct each performance test in Tables 3 and 4 of this subpart that applies to you.

(b) Each performance test must be conducted according to the requirements that this subpart specifies in Table 4 to this subpart. If you own or operate a non-operational stationary RICE that is subject to performance testing, you do not need to start up the engine solely to conduct the performance test. Owners and operators of a non-operational engine can conduct the performance test when the engine is started up again.

(c) [Reserved]

(d) You must conduct three separate test runs for each performance test required in this section, as specified in §63.7(e)(3). Each test run must last at least 1 hour.

(e)(1) You must use Equation 1 of this section to determine compliance with the percent reduction requirement:

$$\frac{C_i - C_o}{C_i} \times 100 = R \quad (\text{Eq. 1})$$

Where:

C_i = concentration of CO or formaldehyde at the control device inlet,

C_o = concentration of CO or formaldehyde at the control device outlet, and

R = percent reduction of CO or formaldehyde emissions.

(2) You must normalize the carbon monoxide (CO) or formaldehyde concentrations at the inlet and outlet of the control device to a dry basis and to 15 percent oxygen, or an equivalent percent carbon dioxide (CO₂). If pollutant concentrations are to be corrected to 15 percent oxygen and CO₂ concentration is measured in lieu of oxygen concentration measurement, a CO₂ correction factor is needed. Calculate the CO₂ correction factor as described in paragraphs (e)(2)(i) through (iii) of this section.

(i) Calculate the fuel-specific F_o value for the fuel burned during the test using values obtained from Method 19, section 5.2, and the following equation:

$$F_o = \frac{0.209 F_d}{F_c} \quad (\text{Eq. 2})$$

Where:

F_o = Fuel factor based on the ratio of oxygen volume to the ultimate CO₂ volume produced by the fuel at zero percent excess air.

0.209 = Fraction of air that is oxygen, percent/100.

F_d = Ratio of the volume of dry effluent gas to the gross calorific value of the fuel from Method 19, dsm³/J (dscf/10⁶ Btu).

F_c = Ratio of the volume of CO₂ produced to the gross calorific value of the fuel from Method 19, dsm³/J (dscf/10⁶ Btu).

(ii) Calculate the CO₂ correction factor for correcting measurement data to 15 percent oxygen, as follows:

$$X_{co_2} = \frac{5.9}{F_o} \quad (\text{Eq. 3})$$

Where:

X_{co_2} = CO₂ correction factor, percent.

5.9 = 20.9 percent O₂ - 15 percent O₂, the defined O₂ correction value, percent.

(iii) Calculate the NO_x and SO₂ gas concentrations adjusted to 15 percent O₂ using CO₂ as follows:

$$C_{adj} = C_d \frac{X_{co_2}}{\%CO_2} \quad (\text{Eq. 4})$$

Where:

%CO₂ = Measured CO₂ concentration measured, dry basis, percent.

(f) If you comply with the emission limitation to reduce CO and you are not using an oxidation catalyst, if you comply with the emission limitation to reduce formaldehyde and you are not using NSCR, or if you comply with the emission limitation to limit the concentration of formaldehyde in the stationary RICE exhaust and you are not using an oxidation catalyst or NSCR, you must petition the Administrator for operating limitations to be established during the initial performance test and continuously monitored thereafter; or for approval of no operating limitations. You must not conduct the initial performance test until after the petition has been approved by the Administrator.

(g) If you petition the Administrator for approval of operating limitations, your petition must include the information described in paragraphs (g)(1) through (5) of this section.

(1) Identification of the specific parameters you propose to use as operating limitations;

(2) A discussion of the relationship between these parameters and HAP emissions, identifying how HAP emissions change with changes in these parameters, and how limitations on these parameters will serve to limit HAP emissions;

(3) A discussion of how you will establish the upper and/or lower values for these parameters which will establish the limits on these parameters in the operating limitations;

(4) A discussion identifying the methods you will use to measure and the instruments you will use to monitor these parameters, as well as the relative accuracy and precision of these methods and instruments; and

(5) A discussion identifying the frequency and methods for recalibrating the instruments you will use for monitoring these parameters.

(h) If you petition the Administrator for approval of no operating limitations, your petition must include the information described in paragraphs (h)(1) through (7) of this section.

(1) Identification of the parameters associated with operation of the stationary RICE and any emission control device which could change intentionally (e.g., operator adjustment, automatic controller adjustment, etc.) or unintentionally (e.g., wear and tear, error, etc.) on a routine basis or over time;

(2) A discussion of the relationship, if any, between changes in the parameters and changes in HAP emissions;

(3) For the parameters which could change in such a way as to increase HAP emissions, a discussion of whether establishing limitations on the parameters would serve to limit HAP emissions;

(4) For the parameters which could change in such a way as to increase HAP emissions, a discussion of how you could establish upper and/or lower values for the parameters which would establish limits on the parameters in operating limitations;

(5) For the parameters, a discussion identifying the methods you could use to measure them and the instruments you could use to monitor them, as well as the relative accuracy and precision of the methods and instruments;

(6) For the parameters, a discussion identifying the frequency and methods for recalibrating the instruments you could use to monitor them; and

(7) A discussion of why, from your point of view, it is infeasible or unreasonable to adopt the parameters as operating limitations.

(i) The engine percent load during a performance test must be determined by documenting the calculations, assumptions, and measurement devices used to measure or estimate the percent load in a specific application. A written report of the average percent load determination must be included in the notification of compliance status. The following information must be included in the written report: the engine model number, the engine manufacturer, the year of purchase, the manufacturer's site-rated brake horsepower, the ambient temperature, pressure, and humidity during the performance test, and all assumptions that

were made to estimate or calculate percent load during the performance test must be clearly explained. If measurement devices such as flow meters, kilowatt meters, beta analyzers, stain gauges, etc. are used, the model number of the measurement device, and an estimate of its accurate in percentage of true value must be provided.

[69 FR 33506, June 15, 2004, as amended at 75 FR 9676, Mar. 3, 2010]

§ 63.6625 What are my monitoring, installation, collection, operation, and maintenance requirements?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

[Link to an amendment published at 75 FR 51589, Aug. 20, 2010.](#)

(a) If you elect to install a CEMS as specified in Table 5 of this subpart, you must install, operate, and maintain a CEMS to monitor CO and either oxygen or CO₂ at both the inlet and the outlet of the control device according to the requirements in paragraphs (a)(1) through (4) of this section.

(1) Each CEMS must be installed, operated, and maintained according to the applicable performance specifications of 40 CFR part 60, appendix B.

(2) You must conduct an initial performance evaluation and an annual relative accuracy test audit (RATA) of each CEMS according to the requirements in §63.8 and according to the applicable performance specifications of 40 CFR part 60, appendix B as well as daily and periodic data quality checks in accordance with 40 CFR part 60, appendix F, procedure 1.

(3) As specified in §63.8(c)(4)(ii), each CEMS must complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each successive 15-minute period. You must have at least two data points, with each representing a different 15-minute period, to have a valid hour of data.

(4) The CEMS data must be reduced as specified in §63.8(g)(2) and recorded in parts per million or parts per billion (as appropriate for the applicable limitation) at 15 percent oxygen or the equivalent CO₂ concentration.

(b) If you are required to install a continuous parameter monitoring system (CPMS) as specified in Table 5 of this subpart, you must install, operate, and maintain each CPMS according to the requirements in §63.8.

(c) If you are operating a new or reconstructed stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, you must monitor and record your fuel usage daily with separate fuel meters to measure the volumetric flow rate of each fuel. In addition, you

must operate your stationary RICE in a manner which reasonably minimizes HAP emissions.

(d) If you are operating a new or reconstructed emergency 4SLB stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions, you must install a non-resettable hour meter prior to the startup of the engine.

(e) If you own or operate an existing stationary RICE with a site rating of less than 100 brake HP located at a major source of HAP emissions, an existing stationary emergency RICE, or an existing stationary RICE located at an area source of HAP emissions not subject to any numerical emission standards shown in Table 2d to this subpart, you must operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.

(f) If you own or operate an existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing emergency stationary RICE located at an area source of HAP emissions, you must install a non-resettable hour meter if one is not already installed.

(g) If you own or operate an existing non-emergency CI engine greater than or equal to 300 HP that is not equipped with a closed crankcase ventilation system, you must comply with either paragraph (g)(1) or paragraph (g)(2) of this section. Owners and operators must follow the manufacturer's specified maintenance requirements for operating and maintaining the open or closed crankcase ventilation systems and replacing the crankcase filters, or can request the Administrator to approve different maintenance requirements that are as protective as manufacturer requirements. Existing CI engines located at area sources in areas of Alaska not accessible by the FAHS do not have to meet the requirements of paragraph (g) in this section.

(1) Install a closed crankcase ventilation system that prevents crankcase emissions from being emitted to the atmosphere, or

(2) Install an open crankcase filtration emission control system that reduces emissions from the crankcase by filtering the exhaust stream to remove oil mist, particulates, and metals.

(h) If you operate a new or existing stationary engine, you must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed

30 minutes, after which time the emission standards applicable to all times other than startup in Tables 1a, 2a, 2c, and 2d to this subpart apply.

(i) If you own or operate a stationary engine that is subject to the work, operation or management practices in items 1, 2, or 4 of Table 2c to this subpart or in items 1 or 4 of Table 2d to this subpart, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d to this subpart. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil before continuing to use the engine. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3606, Jan. 18, 2008; 75 FR 9676, Mar. 3, 2010]

§ 63.6630 How do I demonstrate initial compliance with the emission limitations and operating limitations?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) You must demonstrate initial compliance with each emission and operating limitation that applies to you according to Table 5 of this subpart.

(b) During the initial performance test, you must establish each operating limitation in Tables 1b and 2b of this subpart that applies to you.

(c) You must submit the Notification of Compliance Status containing the results of the initial compliance demonstration according to the requirements in §63.6645.

Continuous Compliance Requirements

§ 63.6635 How do I monitor and collect data to demonstrate continuous compliance?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) If you must comply with emission and operating limitations, you must monitor and collect data according to this section.

(b) Except for monitor malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), you must monitor continuously at all times that the stationary RICE is operating.

(c) You may not use data recorded during monitoring malfunctions, associated repairs, and required quality assurance or control activities in data averages and calculations used to report emission or operating levels. You must, however, use all the valid data collected during all other periods.

§ 63.6640 How do I demonstrate continuous compliance with the emission limitations and operating limitations?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

[Link to an amendment published at 75 FR 51591, Aug. 20, 2010.](#)

(a) You must demonstrate continuous compliance with each emission limitation and operating limitation in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you according to methods specified in Table 6 to this subpart.

(b) You must report each instance in which you did not meet each emission limitation or operating limitation in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you. These instances are deviations from the emission and operating limitations in this subpart. These deviations must be reported according to the requirements in §63.6650. If you change your catalyst, you must reestablish the values of the operating parameters measured during the initial performance test. When you reestablish the values of your operating parameters, you must also conduct a performance test to demonstrate that you are meeting the required emission limitation applicable to your stationary RICE.

(c) [Reserved]

(d) For new, reconstructed, and rebuilt stationary RICE, deviations from the emission or operating limitations that occur during the first 200 hours of operation from engine startup (engine burn-in period) are not violations. Rebuilt stationary RICE means a stationary RICE that has been rebuilt as that term is defined in 40 CFR 94.11(a).

(e) You must also report each instance in which you did not meet the requirements in Table 8 to this subpart that apply to you. If you own or operate a

new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions (except new or reconstructed 4SLB engines greater than or equal to 250 and less than or equal to 500 brake HP), a new or reconstructed stationary RICE located at an area source of HAP emissions, or any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in Table 8 to this subpart: An existing 2SLB stationary RICE, an existing 4SLB stationary RICE, an existing emergency stationary RICE, an existing limited use stationary RICE, or an existing stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis. If you own or operate any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in Table 8 to this subpart, except for the initial notification requirements: a new or reconstructed stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, a new or reconstructed emergency stationary RICE, or a new or reconstructed limited use stationary RICE.

(f) If you own or operate an existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, a new emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions that was installed on or after June 12, 2006, or an existing emergency stationary RICE located at an area source of HAP emissions, you must operate the engine according to the conditions described in paragraphs (f)(1) through (4) of this section.

(1) For owners and operators of emergency engines, any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, as permitted in this section, is prohibited.

(2) There is no time limit on the use of emergency stationary RICE in emergency situations.

(3) You may operate your emergency stationary RICE for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by Federal, State or local government, the manufacturer, the vendor, or the insurance company associated with the engine. Maintenance checks and readiness testing of such units is limited to 100 hours per year. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that Federal, State, or local standards require maintenance and testing of emergency RICE beyond 100 hours per year.

(4) You may operate your emergency stationary RICE up to 50 hours per year in non-emergency situations, but those 50 hours are counted towards the 100 hours per year provided for maintenance and testing. The 50 hours per year for non-emergency situations cannot be used for peak shaving or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity; except that owners and operators may operate the emergency engine for a maximum of 15 hours per year as part of a demand response program if the regional transmission organization or equivalent balancing authority and transmission operator has determined there are emergency conditions that could lead to a potential electrical blackout, such as unusually low frequency, equipment overload, capacity or energy deficiency, or unacceptable voltage level. The engine may not be operated for more than 30 minutes prior to the time when the emergency condition is expected to occur, and the engine operation must be terminated immediately after the facility is notified that the emergency condition is no longer imminent. The 15 hours per year of demand response operation are counted as part of the 50 hours of operation per year provided for non-emergency situations. The supply of emergency power to another entity or entities pursuant to financial arrangement is not limited by this paragraph (f)(4), as long as the power provided by the financial arrangement is limited to emergency power.

[69 FR 33506, June 15, 2004, as amended at 71 FR 20467, Apr. 20, 2006; 73 FR 3606, Jan. 18, 2008; 75 FR 9676, Mar. 3, 2010]

Notifications, Reports, and Records

§ 63.6645 What notifications must I submit and when?

[Link to an amendment published at 75 FR 51591, Aug. 20, 2010.](#)

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) You must submit all of the notifications in §§63.7(b) and (c), 63.8(e), (f)(4) and (f)(6), 63.9(b) through (e), and (g) and (h) that apply to you by the dates specified if you own or operate any of the following;

- (1) An existing stationary CI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions.
- (2) An existing stationary CI RICE located at an area source of HAP emissions.
- (3) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions.
- (4) A new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 HP located at a major source of HAP emissions.

(5) This requirement does not apply if you own or operate an existing stationary CI RICE less than 100 HP, an existing stationary emergency CI RICE, or an existing stationary CI RICE that is not subject to any numerical emission standards.

(b) As specified in §63.9(b)(2), if you start up your stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions before the effective date of this subpart, you must submit an Initial Notification not later than December 13, 2004.

(c) If you start up your new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions on or after August 16, 2004, you must submit an Initial Notification not later than 120 days after you become subject to this subpart.

(d) As specified in §63.9(b)(2), if you start up your stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions before the effective date of this subpart and you are required to submit an initial notification, you must submit an Initial Notification not later than July 16, 2008.

(e) If you start up your new or reconstructed stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions on or after March 18, 2008 and you are required to submit an initial notification, you must submit an Initial Notification not later than 120 days after you become subject to this subpart.

(f) If you are required to submit an Initial Notification but are otherwise not affected by the requirements of this subpart, in accordance with §63.6590(b), your notification should include the information in §63.9(b)(2)(i) through (v), and a statement that your stationary RICE has no additional requirements and explain the basis of the exclusion (for example, that it operates exclusively as an emergency stationary RICE if it has a site rating of more than 500 brake HP located at a major source of HAP emissions).

(g) If you are required to conduct a performance test, you must submit a Notification of Intent to conduct a performance test at least 60 days before the performance test is scheduled to begin as required in §63.7(b)(1).

(h) If you are required to conduct a performance test or other initial compliance demonstration as specified in Tables 4 and 5 to this subpart, you must submit a Notification of Compliance Status according to §63.9(h)(2)(ii).

(1) For each initial compliance demonstration required in Table 5 to this subpart that does not include a performance test, you must submit the Notification of

Compliance Status before the close of business on the 30th day following the completion of the initial compliance demonstration.

(2) For each initial compliance demonstration required in Table 5 to this subpart that includes a performance test conducted according to the requirements in Table 3 to this subpart, you must submit the Notification of Compliance Status, including the performance test results, before the close of business on the 60th day following the completion of the performance test according to §63.10(d)(2).

[73 FR 3606, Jan. 18, 2008, as amended at 75 FR 9677, Mar. 3, 2010]

§ 63.6650 What reports must I submit and when?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) You must submit each report in Table 7 of this subpart that applies to you.

(b) Unless the Administrator has approved a different schedule for submission of reports under §63.10(a), you must submit each report by the date in Table 7 of this subpart and according to the requirements in paragraphs (b)(1) through (b)(9) of this section.

(1) For semiannual Compliance reports, the first Compliance report must cover the period beginning on the compliance date that is specified for your affected source in §63.6595 and ending on June 30 or December 31, whichever date is the first date following the end of the first calendar half after the compliance date that is specified for your source in §63.6595.

(2) For semiannual Compliance reports, the first Compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date follows the end of the first calendar half after the compliance date that is specified for your affected source in §63.6595.

(3) For semiannual Compliance reports, each subsequent Compliance report must cover the semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.

(4) For semiannual Compliance reports, each subsequent Compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.

(5) For each stationary RICE that is subject to permitting regulations pursuant to 40 CFR part 70 or 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6 (a)(3)(iii)(A), you may submit the first and subsequent Compliance reports

according to the dates the permitting authority has established instead of according to the dates in paragraphs (b)(1) through (b)(4) of this section.

(6) For annual Compliance reports, the first Compliance report must cover the period beginning on the compliance date that is specified for your affected source in §63.6595 and ending on December 31.

(7) For annual Compliance reports, the first Compliance report must be postmarked or delivered no later than January 31 following the end of the first calendar year after the compliance date that is specified for your affected source in §63.6595.

(8) For annual Compliance reports, each subsequent Compliance report must cover the annual reporting period from January 1 through December 31.

(9) For annual Compliance reports, each subsequent Compliance report must be postmarked or delivered no later than January 31.

(c) The Compliance report must contain the information in paragraphs (c)(1) through (6) of this section.

(1) Company name and address.

(2) Statement by a responsible official, with that official's name, title, and signature, certifying the accuracy of the content of the report.

(3) Date of report and beginning and ending dates of the reporting period.

(4) If you had a malfunction during the reporting period, the compliance report must include the number, duration, and a brief description for each type of malfunction which occurred during the reporting period and which caused or may have caused any applicable emission limitation to be exceeded. The report must also include a description of actions taken by an owner or operator during a malfunction of an affected source to minimize emissions in accordance with §63.6605(b), including actions taken to correct a malfunction.

(5) If there are no deviations from any emission or operating limitations that apply to you, a statement that there were no deviations from the emission or operating limitations during the reporting period.

(6) If there were no periods during which the continuous monitoring system (CMS), including CEMS and CPMS, was out-of-control, as specified in §63.8(c)(7), a statement that there were no periods during which the CMS was out-of-control during the reporting period.

(d) For each deviation from an emission or operating limitation that occurs for a stationary RICE where you are not using a CMS to comply with the emission or operating limitations in this subpart, the Compliance report must contain the information in paragraphs (c)(1) through (4) of this section and the information in paragraphs (d)(1) and (2) of this section.

(1) The total operating time of the stationary RICE at which the deviation occurred during the reporting period.

(2) Information on the number, duration, and cause of deviations (including unknown cause, if applicable), as applicable, and the corrective action taken.

(e) For each deviation from an emission or operating limitation occurring for a stationary RICE where you are using a CMS to comply with the emission and operating limitations in this subpart, you must include information in paragraphs (c)(1) through (4) and (e)(1) through (12) of this section.

(1) The date and time that each malfunction started and stopped.

(2) The date, time, and duration that each CMS was inoperative, except for zero (low-level) and high-level checks.

(3) The date, time, and duration that each CMS was out-of-control, including the information in §63.8(c)(8).

(4) The date and time that each deviation started and stopped, and whether each deviation occurred during a period of malfunction or during another period.

(5) A summary of the total duration of the deviation during the reporting period, and the total duration as a percent of the total source operating time during that reporting period.

(6) A breakdown of the total duration of the deviations during the reporting period into those that are due to control equipment problems, process problems, other known causes, and other unknown causes.

(7) A summary of the total duration of CMS downtime during the reporting period, and the total duration of CMS downtime as a percent of the total operating time of the stationary RICE at which the CMS downtime occurred during that reporting period.

(8) An identification of each parameter and pollutant (CO or formaldehyde) that was monitored at the stationary RICE.

(9) A brief description of the stationary RICE.

(10) A brief description of the CMS.

(11) The date of the latest CMS certification or audit.

(12) A description of any changes in CMS, processes, or controls since the last reporting period.

(f) Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by 40 CFR 70.6 (a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). If an affected source submits a Compliance report pursuant to Table 7 of this subpart along with, or as part of, the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), and the Compliance report includes all required information concerning deviations from any emission or operating limitation in this subpart, submission of the Compliance report shall be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a Compliance report shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permit authority.

(g) If you are operating as a new or reconstructed stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, you must submit an annual report according to Table 7 of this subpart by the date specified unless the Administrator has approved a different schedule, according to the information described in paragraphs (b)(1) through (b)(5) of this section. You must report the data specified in (g)(1) through (g)(3) of this section.

(1) Fuel flow rate of each fuel and the heating values that were used in your calculations. You must also demonstrate that the percentage of heat input provided by landfill gas or digester gas is equivalent to 10 percent or more of the total fuel consumption on an annual basis.

(2) The operating limits provided in your federally enforceable permit, and any deviations from these limits.

(3) Any problems or errors suspected with the meters.

[69 FR 33506, June 15, 2004, as amended at 75 FR 9677, Mar. 3, 2010]

§ 63.6655 What records must I keep?

[Link to an amendment published at 75 FR 51592, Aug. 20, 2010.](#)

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) If you must comply with the emission and operating limitations, you must keep the records described in paragraphs (a)(1) through (a)(5), (b)(1) through (b)(3) and (c) of this section.

(1) A copy of each notification and report that you submitted to comply with this subpart, including all documentation supporting any Initial Notification or Notification of Compliance Status that you submitted, according to the requirement in §63.10(b)(2)(xiv).

(2) Records of the occurrence and duration of each malfunction of operation (*i.e.*, process equipment) or the air pollution control and monitoring equipment.

(3) Records of performance tests and performance evaluations as required in §63.10(b)(2)(viii).

(4) Records of all required maintenance performed on the air pollution control and monitoring equipment.

(5) Records of actions taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.

(b) For each CEMS or CPMS, you must keep the records listed in paragraphs (b)(1) through (3) of this section.

(1) Records described in §63.10(b)(2)(vi) through (xi).

(2) Previous (*i.e.*, superseded) versions of the performance evaluation plan as required in §63.8(d)(3).

(3) Requests for alternatives to the relative accuracy test for CEMS or CPMS as required in §63.8(f)(6)(i), if applicable.

(c) If you are operating a new or reconstructed stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, you must keep the records of your daily fuel usage monitors.

(d) You must keep the records required in Table 6 of this subpart to show continuous compliance with each emission or operating limitation that applies to you.

(e) You must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan if you own or operate any of the following stationary RICE;

(1) An existing stationary CI RICE with a site rating of less than 100 brake HP located at a major source of HAP emissions.

(2) An existing stationary emergency CI RICE.

(3) An existing stationary CI RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to this subpart.

(f) If you own or operate any of the stationary RICE in paragraphs (f)(1) or (2) of this section, you must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. If the engines are used for demand response operation, the owner or operator must keep records of the notification of the emergency situation, and the time the engine was operated as part of demand response.

(1) An existing emergency stationary CI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions that does not meet the standards applicable to non-emergency engines.

(2) An existing emergency stationary CI RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines.

[69 FR 33506, June 15, 2004, as amended at 75 FR 9678, Mar. 3, 2010]

§ 63.6660 In what form and how long must I keep my records?

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

(a) Your records must be in a form suitable and readily available for expeditious review according to §63.10(b)(1).

(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.

(c) You must keep each record readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to §63.10(b)(1).

[69 FR 33506, June 15, 2004, as amended at 75 FR 9678, Mar. 3, 2010]

Other Requirements and Information

§ 63.6665 What parts of the General Provisions apply to me?

Table 8 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you. If you own or operate a new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions (except new or reconstructed 4SLB engines greater than or equal to 250 and less than or equal to 500 brake HP), a new or reconstructed stationary RICE located at an area source of HAP emissions, or any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with any of the requirements of the General Provisions specified in Table 8: An existing 2SLB stationary RICE, an existing 4SLB stationary RICE, an existing stationary RICE that combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, an existing emergency stationary RICE, or an existing limited use stationary RICE. If you own or operate any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in the General Provisions specified in Table 8 except for the initial notification requirements: A new stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, a new emergency stationary RICE, or a new limited use stationary RICE.

The RICE is an existing spark ignition use engine and does not have to meet the requirements of Subpart ZZZZ and Subpart A of the part.

[75 FR 9678, Mar. 3, 2010]

§ 63.6670 Who implements and enforces this subpart?

The RICE is exempt from this requirement

(a) This subpart is implemented and enforced by the U.S. EPA, or a delegated authority such as your State, local, or tribal agency. If the U.S. EPA Administrator has delegated authority to your State, local, or tribal agency, then that agency (as well as the U.S. EPA) has the authority to implement and enforce this subpart. You should contact your U.S. EPA Regional Office to find out whether this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under 40 CFR part 63, subpart E, the authorities contained in paragraph (c) of this section are retained by the Administrator of the U.S. EPA and are not transferred to the State, local, or tribal agency.

(c) The authorities that will not be delegated to State, local, or tribal agencies are:

(1) Approval of alternatives to the non-opacity emission limitations and operating limitations in §63.6600 under §63.6(g).

(2) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.

(3) Approval of major alternatives to monitoring under §63.8(f) and as defined in §63.90.

(4) Approval of major alternatives to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

(5) Approval of a performance test which was conducted prior to the effective date of the rule, as specified in §63.6610(b).

§ 63.6675 What definitions apply to this subpart?

[Link to an amendment published at 75 FR 51592, Aug. 20, 2010.](#)

Terms used in this subpart are defined in the Clean Air Act (CAA); in 40 CFR 63.2, the General Provisions of this part; and in this section as follows:

Area source means any stationary source of HAP that is not a major source as defined in part 63.

The station is an area source.

Associated equipment as used in this subpart and as referred to in section 112(n)(4) of the CAA, means equipment associated with an oil or natural gas exploration or production well, and includes all equipment from the well bore to the point of custody transfer, except glycol dehydration units, storage vessels with potential for flash emissions, combustion turbines, and stationary RICE.

Black start engine means an engine whose only purpose is to start up a combustion turbine.

CAA means the Clean Air Act (42 U.S.C. 7401 *et seq.*, as amended by Public Law 101-549, 104 Stat. 2399).

Compression ignition means relating to a type of stationary internal combustion engine that is not a spark ignition engine.

Custody transfer means the transfer of hydrocarbon liquids or natural gas: After processing and/or treatment in the producing operations, or from storage vessels or automatic transfer facilities or other such equipment, including product loading racks, to pipelines or any other forms of transportation. For the purposes of this

subpart, the point at which such liquids or natural gas enters a natural gas processing plant is a point of custody transfer.

Deviation means any instance in which an affected source subject to this subpart, or an owner or operator of such a source:

- (1) Fails to meet any requirement or obligation established by this subpart, including but not limited to any emission limitation or operating limitation;
- (2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or
- (3) Fails to meet any emission limitation or operating limitation in this subpart during malfunction, regardless of whether or not such failure is permitted by this subpart.
- (4) Fails to satisfy the general duty to minimize emissions established by §63.6(e)(1)(i).

Diesel engine means any stationary RICE in which a high boiling point liquid fuel injected into the combustion chamber ignites when the air charge has been compressed to a temperature sufficiently high for auto-ignition. This process is also known as compression ignition.

Diesel fuel means any liquid obtained from the distillation of petroleum with a boiling point of approximately 150 to 360 degrees Celsius. One commonly used form is fuel oil number 2. Diesel fuel also includes any non-distillate fuel with comparable physical and chemical properties (e.g. biodiesel) that is suitable for use in compression ignition engines.

Digester gas means any gaseous by-product of wastewater treatment typically formed through the anaerobic decomposition of organic waste materials and composed principally of methane and CO₂.

Dual-fuel engine means any stationary RICE in which a liquid fuel (typically diesel fuel) is used for compression ignition and gaseous fuel (typically natural gas) is used as the primary fuel.

Emergency stationary RICE means any stationary internal combustion engine whose operation is limited to emergency situations and required testing and maintenance. Examples include stationary ICE used to produce power for critical networks or equipment (including power supplied to portions of a facility) when electric power from the local utility (or the normal power source, if the facility runs on its own power production) is interrupted, or stationary ICE used to pump water in the case of fire or flood, etc. Stationary CI ICE used for peak shaving are not

considered emergency stationary ICE. Stationary CI ICE used to supply power to an electric grid or that supply non-emergency power as part of a financial arrangement with another entity are not considered to be emergency engines, except as permitted under §63.6640(f). Emergency stationary RICE with a site-rating of more than 500 brake HP located at a major source of HAP emissions that were installed prior to June 12, 2006, may be operated for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by the manufacturer, the vendor, or the insurance company associated with the engine. Required testing of such units should be minimized, but there is no time limit on the use of emergency stationary RICE in emergency situations and for routine testing and maintenance. Emergency stationary RICE with a site-rating of more than 500 brake HP located at a major source of HAP emissions that were installed prior to June 12, 2006, may also operate an additional 50 hours per year in non-emergency situations. All other emergency stationary RICE must comply with the requirements specified in §63.6640(f).

The RICE is an Emergency Stationary RICE. Operation is limited to emergency situations and required testing and maintenance (usually once per month). The RICE is used to produce power for critical station functions in the event that electric power from the local utility is lost. The station must continue to operate and pump gas to distribution points. Since the unit is existing, it does not need to meet the requirements of subpart ZZZZ.

Engine startup means the time from initial start until applied load and engine and associated equipment reaches steady state or normal operation. For stationary engine with catalytic controls, engine startup means the time from initial start until applied load and engine and associated equipment, including the catalyst, reaches steady state or normal operation.

Four-stroke engine means any type of engine which completes the power cycle in two crankshaft revolutions, with intake and compression strokes in the first revolution and power and exhaust strokes in the second revolution.

Gaseous fuel means a material used for combustion which is in the gaseous state at standard atmospheric temperature and pressure conditions.

Gasoline means any fuel sold in any State for use in motor vehicles and motor vehicle engines, or nonroad or stationary engines, and commonly or commercially known or sold as gasoline.

Glycol dehydration unit means a device in which a liquid glycol (including, but not limited to, ethylene glycol, diethylene glycol, or triethylene glycol) absorbent directly contacts a natural gas stream and absorbs water in a contact tower or absorption column (absorber). The glycol contacts and absorbs water vapor and other gas stream constituents from the natural gas and becomes "rich" glycol.

This glycol is then regenerated in the glycol dehydration unit reboiler. The "lean" glycol is then recycled.

Hazardous air pollutants (HAP) means any air pollutants listed in or pursuant to section 112(b) of the CAA.

ISO standard day conditions means 288 degrees Kelvin (15 degrees Celsius), 60 percent relative humidity and 101.3 kilopascals pressure.

Landfill gas means a gaseous by-product of the land application of municipal refuse typically formed through the anaerobic decomposition of waste materials and composed principally of methane and CO₂.

Lean burn engine means any two-stroke or four-stroke spark ignited engine that does not meet the definition of a rich burn engine.

Limited use stationary RICE means any stationary RICE that operates less than 100 hours per year.

Liquefied petroleum gas means any liquefied hydrocarbon gas obtained as a by-product in petroleum refining of natural gas production.

Liquid fuel means any fuel in liquid form at standard temperature and pressure, including but not limited to diesel, residual/crude oil, kerosene/naphtha (jet fuel), and gasoline.

Major Source, as used in this subpart, shall have the same meaning as in §63.2, except that:

- (1) Emissions from any oil or gas exploration or production well (with its associated equipment (as defined in this section)) and emissions from any pipeline compressor station or pump station shall not be aggregated with emissions from other similar units, to determine whether such emission points or stations are major sources, even when emission points are in a contiguous area or under common control;
- (2) For oil and gas production facilities, emissions from processes, operations, or equipment that are not part of the same oil and gas production facility, as defined in §63.1271 of subpart HHH of this part, shall not be aggregated;
- (3) For production field facilities, only HAP emissions from glycol dehydration units, storage vessel with the potential for flash emissions, combustion turbines and reciprocating internal combustion engines shall be aggregated for a major source determination; and

(4) Emissions from processes, operations, and equipment that are not part of the same natural gas transmission and storage facility, as defined in §63.1271 of subpart HHH of this part, shall not be aggregated.

Malfunction means any sudden, infrequent, and not reasonably preventable failure of air pollution control equipment, process equipment, or a process to operate in a normal or usual manner which causes, or has the potential to cause, the emission limitations in an applicable standard to be exceeded. Failures that are caused in part by poor maintenance or careless operation are not malfunctions.

Natural gas means a naturally occurring mixture of hydrocarbon and non-hydrocarbon gases found in geologic formations beneath the Earth's surface, of which the principal constituent is methane. Natural gas may be field or pipeline quality.

Non-selective catalytic reduction (NSCR) means an add-on catalytic nitrogen oxides (NO_x) control device for rich burn engines that, in a two-step reaction, promotes the conversion of excess oxygen, NO_x, CO, and volatile organic compounds (VOC) into CO₂, nitrogen, and water.

Oil and gas production facility as used in this subpart means any grouping of equipment where hydrocarbon liquids are processed, upgraded (*i.e.*, remove impurities or other constituents to meet contract specifications), or stored prior to the point of custody transfer; or where natural gas is processed, upgraded, or stored prior to entering the natural gas transmission and storage source category. For purposes of a major source determination, facility (including a building, structure, or installation) means oil and natural gas production and processing equipment that is located within the boundaries of an individual surface site as defined in this section. Equipment that is part of a facility will typically be located within close proximity to other equipment located at the same facility. Pieces of production equipment or groupings of equipment located on different oil and gas leases, mineral fee tracts, lease tracts, subsurface or surface unit areas, surface fee tracts, surface lease tracts, or separate surface sites, whether or not connected by a road, waterway, power line or pipeline, shall not be considered part of the same facility. Examples of facilities in the oil and natural gas production source category include, but are not limited to, well sites, satellite tank batteries, central tank batteries, a compressor station that transports natural gas to a natural gas processing plant, and natural gas processing plants.

Oxidation catalyst means an add-on catalytic control device that controls CO and VOC by oxidation.

Peaking unit or engine means any standby engine intended for use during periods of high demand that are not emergencies.

Percent load means the fractional power of an engine compared to its maximum manufacturer's design capacity at engine site conditions. Percent load may range between 0 percent to above 100 percent.

Potential to emit means the maximum capacity of a stationary source to emit a pollutant under its physical and operational design. Any physical or operational limitation on the capacity of the stationary source to emit a pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored, or processed, shall be treated as part of its design if the limitation or the effect it would have on emissions is federally enforceable. For oil and natural gas production facilities subject to subpart HH of this part, the potential to emit provisions in §63.760(a) may be used. For natural gas transmission and storage facilities subject to subpart HHH of this part, the maximum annual facility gas throughput for storage facilities may be determined according to §63.1270(a)(1) and the maximum annual throughput for transmission facilities may be determined according to §63.1270(a)(2).

Production field facility means those oil and gas production facilities located prior to the point of custody transfer.

Production well means any hole drilled in the earth from which crude oil, condensate, or field natural gas is extracted.

Propane means a colorless gas derived from petroleum and natural gas, with the molecular structure C_3H_8 .

Residential/commercial/institutional emergency stationary RICE means an emergency stationary RICE used in residential establishments such as homes or residences, commercial establishments such as office buildings, hotels, or stores, or institutional establishments such as medical centers, research centers, and institutions of higher education.

Responsible official means responsible official as defined in 40 CFR 70.2.

Rich burn engine means any four-stroke spark ignited engine where the manufacturer's recommended operating air/fuel ratio divided by the stoichiometric air/fuel ratio at full load conditions is less than or equal to 1.1. Engines originally manufactured as rich burn engines, but modified prior to December 19, 2002 with passive emission control technology for NO_x (such as pre-combustion chambers) will be considered lean burn engines. Also, existing engines where there are no manufacturer's recommendations regarding air/fuel ratio will be considered a rich burn engine if the excess oxygen content of the exhaust at full load conditions is less than or equal to 2 percent.

Site-rated HP means the maximum manufacturer's design capacity at engine site conditions.

Spark ignition means relating to either: A gasoline-fueled engine; or any other type of engine a spark plug (or other sparking device) and with operating characteristics significantly similar to the theoretical Otto combustion cycle. Spark ignition engines usually use a throttle to regulate intake air flow to control power during normal operation. Dual-fuel engines in which a liquid fuel (typically diesel fuel) is used for CI and gaseous fuel (typically natural gas) is used as the primary fuel at an annual average ratio of less than 2 parts diesel fuel to 100 parts total fuel on an energy equivalent basis are spark ignition engines.

Stationary reciprocating internal combustion engine (RICE) means any reciprocating internal combustion engine which uses reciprocating motion to convert heat energy into mechanical work and which is not mobile. Stationary RICE differ from mobile RICE in that a stationary RICE is not a non-road engine as defined at 40 CFR 1068.30, and is not used to propel a motor vehicle or a vehicle used solely for competition.

Stationary RICE test cell/stand means an engine test cell/stand, as defined in subpart PPPPP of this part, that tests stationary RICE.

Stoichiometric means the theoretical air-to-fuel ratio required for complete combustion.

Storage vessel with the potential for flash emissions means any storage vessel that contains a hydrocarbon liquid with a stock tank gas-to-oil ratio equal to or greater than 0.31 cubic meters per liter and an American Petroleum Institute gravity equal to or greater than 40 degrees and an actual annual average hydrocarbon liquid throughput equal to or greater than 79,500 liters per day. Flash emissions occur when dissolved hydrocarbons in the fluid evolve from solution when the fluid pressure is reduced.

Subpart means 40 CFR part 63, subpart ZZZZ.

Surface site means any combination of one or more graded pad sites, gravel pad sites, foundations, platforms, or the immediate physical location upon which equipment is physically affixed.

Two-stroke engine means a type of engine which completes the power cycle in single crankshaft revolution by combining the intake and compression operations into one stroke and the power and exhaust operations into a second stroke. This system requires auxiliary scavenging and inherently runs lean of stoichiometric.

[69 FR 33506, June 15, 2004, as amended at 71 FR 20467, Apr. 20, 2006; 73 FR 3607, Jan. 18, 2008; 75 FR 9679, Mar. 3, 2010]

40 CFR 63 Subpart DDDDD – NESHAP for Industrial, Commercial, and Institutional Boilers and Process Heaters

The Industrial/Commercial/Institutional Boilers and Process Heaters MACT for major sources was promulgated on March 21, 2011, and regulates HAP emissions from new and existing industrial, commercial, or institutional boilers and process heaters located at major sources of HAP emissions. The EPA subsequently issued a notice on May 18, 2011 to postpone the effective dates of the final rule until the completion of reconsideration or judicial review, whichever is earlier. On January 9, 2012, the EPA vacated the May 18, 2011 notice that delayed the effective dates of the Boiler MACT rule. The notice on final action on reconsideration was published in the Federal Register on January 31, 2013. The Compressor Station 3 and 4 are not a major source of HAPs; therefore this regulation does not apply.

40 CFR 60 Subpart IIII – Standards of Performance for Compression Ignition Internal Combustion Engines (CI ICE)

This regulation applies to owners or operators of stationary CI ICE that commence construction, modification or reconstruction after July 11, 2005 and to manufacturers of 2007 and later model year CI ICE. The GTN Compressor Station 3 and 4 does not operate CI ICE therefore; this regulation is not applicable to this facility.

40 CFR 60 Subpart JJJJ – Standards of Performance for Stationary Spark Ignition Internal Combustion Engines (SI ICE)

On March 18th, 2008, US EPA finalized Standards for Performance for Stationary Spark Ignition Internal Combustion Engines (SI ICE) and National Emission Standards for Hazardous Air Pollutants (NESHAP) for Reciprocating Internal Combustion Engines (RICE). Emergency Engines at The GTN Compressor Station 3 and 4 is exempt from this regulation because the emergency engines was manufactured before January 1, 2009 (40 CFR 60 Subpart JJJJ 60.4230 (3)(iv)). Therefore, Subpart JJJJ does not apply to the emergency engines at the GTN Compressor Stations 3 and 4.

40 CFR 60 Subpart KKK-Standards of Performance for Equipment Leaks of VOC from Onshore Natural Gas Processing Plants

The Compressor Station 3 and 4 is not a natural gas processing plant as defined in the regulation. The facility does not engage in extraction of natural gas liquids from field gas or fractionate mixed natural gas liquids to natural gas products. Therefore, this regulation is not applicable.



**Air Quality
TIER I OPERATING PERMIT**
**State of Idaho
Department of Environmental Quality**

PERMIT No.: T1-2010.0099
FACILITY ID No.: 021-00013
AQCR: 063 **CLASS:** A **ZONE:** 11
SIC: 4922 **NAICS:** 486210
UTM COORDINATE (km): 560.64, 5423.7

1. PERMITTEE

TransCanada, Gas Transmission Northwest, Compressor Station 3

2. PROJECT DESCRIPTION

Project # 60553 Tier I Operating Permit Renewal

3. MAILING ADDRESS

201 W. North River Dr. Suite 505

CITY

Spokane

STATE

WA

ZIP

99201

4. FACILITY CONTACT

~~Stanley D. Barry~~ Lionel Philip

TITLE

Air Quality Specialist

TELEPHONE

(832) 320-5127

5. RESPONSIBLE OFFICIAL

Ken Leier

TITLE

Regional Director, Pipeline
Operations and Maintenance

TELEPHONE

(503) 533-2831

6. EXACT PLANT LOCATION

Highway 95, approximately 2.2 miles south of Eastport

COUNTY

Kootenai

7. GENERAL NATURE OF BUSINESS & KINDS OF PRODUCTS

Natural gas pipeline compressor station

8. PERMIT AUTHORITY

This Tier I operating permit is issued pursuant to the Rules for the Control of Air Pollution in Idaho, IDAPA 58.01.01.300 through 386. The permittee shall comply with the terms and conditions of this permit.

This permit incorporates all applicable terms and conditions of prior air quality permits issued by the Idaho Department of Environmental Quality (DEQ) for the permitted source, unless the permittee emits toxic pollutants subject to state-only requirements pursuant to IDAPA 58.01.01.210, and the permittee elects not to incorporate those terms and conditions into this operating permit.

The effective date of this permit is the date of signature by DEQ on the cover page.

CAROLE ZUNDEL, PERMIT WRITER
DEPARTMENT OF ENVIRONMENTAL QUALITY

MIKE SIMON, STATIONARY SOURCE PROGRAM MANAGER
DEPARTMENT OF ENVIRONMENTAL QUALITY

DATE ISSUED:

March 7, 2011

DATE MODIFIED/AMENDED:

DATE EXPIRES:

March 7, 2016

Table of Contents

ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURE	3
1. TIER I OPERATING PERMIT SCOPE	4
2. FACILITY-WIDE CONDITIONS.....	5
3. UNIT 3A - COOPER-ROLLS COBERRA 125 WITH DIFFUSION FLAME BURNER.....	17
4. UNIT 3B-COOPER-ROLLS COBERRA 6000 WITH DRY LOW EMISSIONS COMBUSTOR	19
5. INSIGNIFICANT ACTIVITIES.....	25
6. TIER I OPERATING PERMIT GENERAL PROVISIONS	26

Acronyms, Units, and Chemical Nomenclature

AIRS	Aerometric Information Retrieval System
AQCR	Air Quality Control Region
ASTM	American Society for Testing and Materials
BACT	Best Available Control Technology
Btu/scf	British thermal unit per standard cubic foot
CAA	Clean Air Act
CFR	Code of Federal Regulations
CO	carbon monoxide
DEQ	Department of Environmental Quality
EPA	U.S. Environmental Protection Agency
gr/dscf	grains (1 lb = 7,000 grains) per dry standard cubic foot
HAP	hazardous air pollutants
hr/yr	hours per year
IDAPA	a numbering designation for all administrative rules in Idaho promulgated in accordance with the Idaho Administrative Procedures Act
km	kilometers
lb/hr	pounds per hour
m	meters
MACT	Maximum Achievable Control Technology
NAICS	North American Industry Classification System
NESHAP	National Emission Standards for Hazardous Air Pollutants
NO ₂	nitrogen dioxide
NO _x	nitrogen oxides
NSPS	New Source Performance Standards
PM	particulate matter
PM ₁₀	particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers
ppm	parts per million
PSD	Prevention of Significant Deterioration
PTC	permit to construct
PTE	potential to emit
RICE	reciprocating internal combustion engine
SIC	Standard Industrial Classification
SIP	State Implementation Plan
SO ₂	sulfur dioxide
T/yr	tons per year
TAP	toxic air pollutants
U.S.C.	United States Code
UTM	Universal Transverse Mercator
VOC	volatile organic compounds

1. TIER I OPERATING PERMIT SCOPE

Purpose

- 1.1 This Tier I operating permit establishes facility-wide requirements in accordance with the Idaho State Implementation Plan control strategy and the Rules.

The purpose of this permitting action is to renew the Tier I operating permit.

- 1.2 This Tier I permit incorporates the following permit(s):

Permit to Construct No. P-000109, issued June 14, 2000

- 1.3 This Tier I operating permit supersedes the following permit:

Tier I Operating Permit No. TI-2009.0034, issued January 26, 2007

Regulated Sources

- 1.4 Table 1.1 lists all sources of emissions regulated in this Tier I operating permit.

Table 1.1 REGULATED SOURCES

Permit Section	Source Description	Emissions Control
3	Unit 3A-Cooper-Rolls Coberra 125 with Diffusion Flame Burner, in operation since 1969.	None
4	Unit 3B-Cooper-Rolls Coberra 6000 with Dry Low Emissions (DLE) Combustor for NOx control and an output capacity of 35,000 hp, constructed in 1993.	None
5	Emergency generator >500 bhp	None

2. FACILITY-WIDE CONDITIONS

Table 2.1 contains a summary of requirements that apply generally to emissions units at the facility.

Table 2.1 APPLICABLE REQUIREMENTS SUMMARY

Permit Condition	Parameter	Permit Limit/ Standard Summary	Applicable Requirements Reference	Operating, Monitoring and Recordkeeping Requirements
2.1	Fugitive Dust	Reasonable Control	IDAPA 58.01.01.650-651	2.2, 2.3, 2.4, 2.11, 2.12
2.5	Odors	Reasonable Control	IDAPA 58.01.01.775-776	2.6, 2.11, 2.12
2.7	Visible emissions	20% opacity for no more than three minutes in any 60-minute period	IDAPA 58.01.01.625	2.8, 2.11, 2.12
2.9	Excess emissions	Compliance with IDAPA 58.01.01.130-136	IDAPA 58.01.01.130-136	2.9.1-2.9.5, 2.10, 2.11
2.11	Criteria air pollutants, opacity	Performance/Compliance testing	IDAPA 58.01.01.157	2.10, 2.11, 2.12
2.10	Air quality standards	EPA Reference Test Methods	IDAPA 58.01.01.157	2.10, 2.11, 2.12
2.13	Fuel-burning equipment	0.015 gr/dscf @ 3% O ₂ , for gas 0.050 gr/dscf @ 3% O ₂ , for liquid	IDAPA 58.01.01.677	2.11
2.14	Open burning	Compliance with IDAPA 58.01.01.600-616	IDAPA 58.01.01.600-616	2.11
2.15	Renovation and demolition	Compliance with 40 CFR 61, Subpart M	40 CFR 61, Subpart M	2.11
2.16	Chemical accident release provisions	Compliance with 40 CFR 68	40 CFR 68	2.11
2.17	Recycling and emissions reductions	Compliance with 40 CFR 82, Subpart F	40 CFR 82, Subpart F	2.11
2.18-2.26	NSPS	Compliance with applicable subparts	40 CFR 60	2.11

Fugitive Dust

2.1 All reasonable precautions shall be taken to prevent PM from becoming airborne in accordance with IDAPA 58.01.01.650-651.

[IDAPA 58.01.01.650-651, 3/30/07]

2.2 The permittee shall monitor and maintain records of the frequency and the method(s) used (e.g., water, chemical dust suppressants) to reasonably control fugitive dust emissions.

[IDAPA 58.01.01.322.06, 07, 5/1/94]

2.3 The permittee shall maintain records of all fugitive dust complaints received. The permittee shall take appropriate corrective action as expeditiously as practicable after receipt of a valid complaint. The records shall include, at a minimum, the date that each complaint was received and a description of the following: the complaint, the permittee's assessment of the validity of the complaint, any corrective action taken, and the date the corrective action was taken.

[IDAPA 58.01.01.322.06, 07, 5/1/94]

2.4 The permittee shall incorporate and follow a dust mitigation plan to reduce fugitive dust emissions or shall conduct a quarterly facility-wide inspection of potential sources of fugitive dust emissions, during daylight hours and under normal operating conditions to ensure that the methods used to reasonably control fugitive dust emissions are effective. If fugitive dust emissions are not being

Comment [A1]: TransCanada is requesting that the facility comply with the state Dust Mitigation

reasonably controlled, the permittee shall take corrective action as expeditiously as practicable. The permittee shall maintain records of the results of each fugitive dust emissions inspection. The records shall include, at a minimum, the date of each inspection and a description of the following: the permittee's assessment of the conditions existing at the time fugitive emissions were present (if observed), any corrective action taken in response to the fugitive dust emissions, and the date the corrective action was taken.

[IDAPA 58.01.01.322.06, 07, 5/1/94]

Comment:

TransCanada would like to remove the requirement to conduct and record of dust emission inspections and instead implement a site specific dust mitigation plan.

TransCanada is proposing the following:

- 1) that when there is disturbed soil, "reasonable precautions" will be taken to prevent dust
- 2) we will follow the pdf guidance below: <http://adminrules.idaho.gov/rules/2011/58/0101.pdf>
- 3) TransCanada will have gravel which is a dust control measure
- 4) Speed limit onsite at all times will be limited to 10 mph or 15 mph
- 5) Minimal traffic onsite measures

<http://adminrules.idaho.gov/rules/2011/58/0101.pdf>

650.RULES FOR CONTROL OF FUGITIVE DUST.

651.GENERAL RULES. The purpose of Sections 650 through 651 is to require that all reasonable precautions be taken to prevent the generation of fugitive dust. (5-1-94)

All reasonable precautions shall be taken to prevent particulate matter from becoming airborne. In determining what is reasonable, consideration will be given to factors such as the proximity of dust emitting operations to human habitations and/or activities, the proximity to mandatory Class I Federal Areas and atmospheric conditions which might affect the movement of particulate matter. Some of the reasonable precautions may include, but are not limited to, the following: (3-30-07) **01. Use of Water or Chemicals.** Use, where practical, of water or chemicals for control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads, or the clearing of land. (5-1-94) **02. Application of Dust Suppressants.** Application, where practical, of asphalt, oil, water or suitable chemicals to, or covering of dirt roads, material stockpiles, and other surfaces which can create dust. (5-1-94) **03. Use of Control Equipment.** Installation and use, where practical, of hoods, fans and fabric filters or equivalent systems to enclose and vent the handling of dusty materials. Adequate containment methods should be employed during sandblasting or other operations. (5-1-94) **04. Covering of Trucks.** Covering, when practical, open bodied trucks transporting materials likely to give rise to airborne dusts. (5-1-94) **05. Paving.** Paving of roadways and their maintenance in a clean condition, where practical. (5-1-94) **06. Removal of Materials.** Prompt removal of earth or other stored material from streets, where practical.

Odors

- 2.5 The permittee shall not allow, suffer, cause, or permit the emission of odorous gases, liquids, or solids to the atmosphere in such quantities as to cause air pollution.

[IDAPA 58.01.01.775-776 (state only), 5/1/94]

- 2.6 The permittee shall maintain records of all odor complaints received. If the complaint has merit, the permittee shall take appropriate corrective action as expeditiously as practicable. The records shall include, at a minimum, the date each complaint was received and a description of the following: the complaint, the permittee's assessment of the validity of the complaint, any corrective action taken, and the date the corrective action was taken.

[IDAPA 58.01.01.322.06, 07 (state-only), 5/1/94]

Visible Emissions

- 2.7 The permittee shall not discharge any air pollutant to the atmosphere from any point of emission for a period or periods aggregating more than three minutes in any 60-minute period which is greater than 20% opacity as determined by procedures contained in IDAPA 58.01.01.625. These provisions shall not apply when the presence of uncombined water, nitrogen oxides, and/or chlorine gas is the only reason for the failure of the emission to comply with the requirements of this section.

[IDAPA 58.01.01.625, 4/5/00]

- 2.8 The permittee shall conduct a quarterly facility-wide inspection of potential sources of visible emissions, during daylight hours and under normal operating conditions. Sources that are monitored using a continuous opacity monitoring system (COMS) are not required to comply with this permit condition. The inspection shall consist of a see/no see evaluation for each potential source of visible emissions. If any visible emissions are present from any point of emission, the permittee shall either

a) take appropriate corrective action as expeditiously as practicable to eliminate the visible emissions. Within 24 hours of the initial see/no see evaluation and after the corrective action, the permittee shall conduct a see/no see evaluation of the emissions point in question. If the visible emissions are not eliminated, the permittee shall comply with b).

or

b) perform a Method 9 opacity test in accordance with the procedures outlined in IDAPA 58.01.01.625. A minimum of 30 observations shall be recorded when conducting the opacity test. If opacity is greater than 20%, as measured using Method 9, for a period or periods aggregating more than three minutes in any 60-minute period, the permittee shall take all necessary corrective action and report the exceedance in its annual compliance certification and in accordance with IDAPA 58.01.01.130-136.

The permittee shall maintain records of the results of each visible emission inspection and each opacity test when conducted. The records shall include, at a minimum, the date and results of each inspection and test and a description of the following: the permittee's assessment of the conditions existing at the time visible emissions are present (if observed), any corrective action taken in response to the visible emissions, and the date corrective action was taken.

[IDAPA 58.01.01.322.06, 07, 5/1/94; IDAPA 58.01.01.322.08, 4/5/00]

Excess Emissions

Excess Emissions - General

- 2.9 The permittee shall comply with the procedures and requirements of IDAPA 58.01.01.130-136 for excess emissions. The provisions of IDAPA 58.01.01.130-136 shall govern in the event of conflicts between Permit Condition 2.9 and the regulations of IDAPA 58.01.01.130-136.
- 2.9.1 The person responsible for or in charge of a facility during an excess emissions event shall, with all practicable speed, initiate and complete appropriate and reasonable action to correct the conditions causing the excess emissions event; to reduce the frequency of occurrence of such events; to minimize the amount by which the emission standard is exceeded; and shall, as provided below or upon request of DEQ, submit a full report of such occurrence, including a statement of all known causes, and of the scheduling and nature of the actions to be taken.

[IDAPA 58.01.01.132, 4/5/00]

Excess Emissions – Startup, Shutdown, Scheduled Maintenance

2.9.2 In all cases where startup, shutdown, or scheduled maintenance of any equipment or emission unit is expected to result or results in an excess emissions event, the owner or operator of the facility or emissions unit generating the excess emissions shall demonstrate compliance with IDAPA 58.01.01.133.01(a) through (d), including, but not limited to, the following:

[IDAPA 58.01.01.133, 4/5/00]

- A prohibition of any scheduled startup, shutdown, or maintenance resulting in excess emissions shall occur during any period in which an Atmospheric Stagnation Advisory or a Wood Stove Curtailment Advisory has been declared by DEQ.
- Notifying DEQ of the excess emissions event as soon as reasonably possible, but no later than two hours prior to, the start of the event, unless the owner or operator demonstrates to DEQ's satisfaction that a shorter advance notice was necessary.
- The owner or operator of a source of excess emissions shall report and record the information required pursuant to Permit Conditions 2.9.4 and 2.9.5 and IDAPA 58.01.01.135 and 136 for each excess emissions event due to startup, shutdown, or scheduled maintenance.

[IDAPA 58.01.01.133.01.a, 3/20/97]

[IDAPA 58.01.01.133.01.b, 4/5/00]

[IDAPA 58.01.01.133.01.c, 3/20/97]

Excess Emissions – Upset, Breakdown, or Safety Measures

2.9.3 In all cases where upset or breakdown of equipment or an emissions unit, or the initiation of safety measures, results or may result in an excess emissions event, the owner or operator of the facility or emissions unit generating the excess emissions shall demonstrate compliance with IDAPA 58.01.01.134.01(a) and (b) and the following:

[IDAPA 58.01.01.134, 4/11/06]

2.9.3.1 For all equipment or emissions units from which excess emissions result during upset or breakdown conditions, or for other situations that may necessitate the implementation of safety measures which cause excess emissions, the facility owner or operator shall comply with the following:

[IDAPA 58.01.01.134.02, 4/5/00]

The owner or operator shall immediately undertake all appropriate measures to reduce and, to the extent possible, eliminate excess emissions resulting from the event and to minimize the impact of such excess emissions on the ambient air quality and public health.

[IDAPA 58.01.01.134.02.a, 4/5/00]

The owner or operator shall notify DEQ of any upset, breakdown, or safety event that results in excess emissions. Such notification shall identify the time, specific location, equipment or emissions unit involved, and (to the extent known) the cause(s) of the occurrence. The notification shall be given as soon as reasonably possible, but no later than 24 hours after the event, unless the owner or operator demonstrates to DEQ's satisfaction that the longer reporting period was necessary.

[IDAPA 58.01.01.134.02.b, 4/5/00]

The owner or operator shall report and record the information required pursuant to Permit Conditions 2.9.4 and 2.9.5 and IDAPA 58.01.01.135 and 136 for each excess emissions event caused by an upset, breakdown, or safety measure.

[IDAPA 58.01.01.134.02.c, 3/20/97]

- 2.9.3.2 During any period of excess emissions caused by upset, breakdown, or operation under facility safety measures, DEQ may require the owner or operator to immediately reduce or cease operation of the equipment or emissions unit causing the period until such time as the condition causing the excess has been corrected or brought under control. Such action by DEQ shall be taken upon consideration of the factors listed in IDAPA 58.01.01.134.03 and after consultation with the facility owner or operator.
[IDAPA 58.01.01.134.03 4/5/00]

Excess Emissions – Reporting and Recordkeeping

- 2.9.4 A written report for each excess emissions event shall be submitted to DEQ by the owner or operator no later than 15 days after the beginning of such an event. Each report shall contain the information specified in IDAPA 58.01.01.135.02.
[IDAPA 58.01.01.135.01 and 02, 4/11/06]

- 2.9.5 The owner or operator shall maintain excess emissions records at the facility for the most recent five-calendar-year period. The excess emissions records shall be made available to DEQ upon request and shall include the information requested by IDAPA 58.01.01.136.03(a) and (b) as summarized in the following:
[IDAPA 58.01.01.136.01, 02, 3/20/97; IDAPA 58.01.01.136.03, 4/5/00]

- An excess emissions log book for each emissions unit or piece of equipment containing copies of all reports that have been submitted to DEQ pursuant to IDAPA 58.01.01.135 for the particular emissions unit or equipment; and
[IDAPA 58.01.01.136.03.a, 4/5/00]
- Copies of all startup, shutdown, and scheduled maintenance procedures and upset, breakdown, or safety preventative maintenance plans that have been developed by the owner or operator in accordance with IDAPA 58.01.01.133 and 134, and facility records as necessary to demonstrate compliance with such procedures and plans.
[IDAPA 58.01.01.136.03.b, 3/20/97]

Performance Testing

- 2.10 If performance testing is required, the permittee shall provide notice of intent to test to DEQ at least 15 days prior to the scheduled test or shorter time period as provided in a permit, order, consent decree, or by DEQ approval. DEQ may, at its option, have an observer present at any emissions tests conducted on a source. DEQ requests such testing not be performed on weekends or state holidays.

All testing shall be conducted in accordance with the procedures in IDAPA 58.01.01.157. Without prior DEQ approval, any alternative testing is conducted solely at the permittee's risk. If the permittee fails to obtain prior written approval by DEQ for any testing deviations, DEQ may determine that the testing does not satisfy the testing requirements. Therefore, prior to conducting any performance test, the permittee is encouraged to submit in writing to DEQ, at least 30 days in advance, the following for approval:

- The type of method to be used
- Any extenuating or unusual circumstances regarding the proposed test
- The proposed schedule for conducting and reporting the test

Unless a longer time is approved by DEQ, the permittee shall submit a compliance test report for the respective test to DEQ within 30 days following the date in which a compliance test required by this permit is concluded. The compliance test report shall include all process operating data collected

during the test period as well as the test results, raw test data, and associated documentation, including any approved test protocol.

The proposed test date(s), test date rescheduling notice(s), compliance test report, and all other correspondence shall be sent to the following address:

Air Quality Permit Compliance
Department of Environmental Quality
Coeur d'Alene Regional Office
2110 Ironwood Pkwy
Coeur d'Alene, ID 83814
Phone: (208) 769-1422 Fax: (208) 769-1404
[IDAPA 58.01.01.157, 4/5/00; IDAPA 58.01.01.322.06, 08.a, 09, 5/1/94]

Monitoring and Recordkeeping

- 2.11 The permittee shall maintain sufficient records to assure compliance with all of the terms and conditions of this operating permit. Records of monitoring information shall include, but not be limited to, the following: (a) the date, place, and times of sampling or measurements; (b) the date analyses were performed; (c) the company or entity that performed the analyses; (d) the analytical techniques or methods used; (e) the results of such analyses; and (f) the operating conditions existing at the time of sampling or measurement. All monitoring records and support information shall be retained for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes, but is not limited to, all calibration and maintenance records, all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. All records required to be maintained by this permit shall be made available in either hard copy or electronic format to DEQ representatives upon request.
[IDAPA 58.01.01.322.07, 5/1/94]

Reports and Certifications

- 2.12 All periodic reports and certifications required by this permit shall be submitted to DEQ within 30 days of the end of each specified reporting period. Excess emissions reports and notifications shall be submitted in accordance with IDAPA 58.01.01.130-136. Reports, certifications, and notifications shall be submitted to:

Air Quality Permit Compliance
Department of Environmental Quality
Coeur d'Alene Regional Office
2110 Ironwood Pkwy
Coeur d'Alene, ID 83814
Phone: (208) 769-1422 Fax: (208) 769-1404

The periodic compliance certification required by General Provision 21 shall also be submitted within 30 days of the end of the specified reporting period to:

EPA Region 10
Air Operating Permits, OAQ-107
1200 Sixth Ave.
Seattle, WA 98101

[IDAPA 58.01.01.322.08, 11, 5/1/94]

Fuel-Burning Equipment

2.13 The permittee shall not discharge PM to the atmosphere from any fuel-burning equipment in excess of 0.015 gr/dscf of effluent gas corrected to 3% oxygen by volume for gas, 0.050 gr/dscf of effluent gas corrected to 3% oxygen by volume for liquid, 0.050 gr/dscf of effluent gas corrected to 8% oxygen by volume for coal, and 0.080 gr/dscf of effluent gas corrected to 8% oxygen by volume for wood products.

[IDAPA 58.01.01.676-677, 5/1/94]

Comment: 2.13 should be removed as it is not applicable. Units 3A and 3B are not “fuel burning equipment” as defined by IDAPA 58.01.01.006.45 and not subject to this standard. The two gas fired space heating boilers are certified annually by Ken Leier, GTN Regional Director, Pipeline Operations and Maintenance to meet this emission limit. Exclusive use of pipeline grade natural gas ensures PM limits are met.

Open Burning

2.14 The permittee shall comply with the *Rules for Control of Open Burning*, IDAPA 58.01.01.600-623.

[IDAPA 58.01.01.600-623, 04/02/08T]
[40 CFR 61, Subpart M]

Asbestos

2.15 The permittee shall comply with all applicable portions of 40 CFR 61, Subpart M – Asbestos.

[40 CFR 61, Subpart M]

Regulated Substances for Accidental Release Prevention

2.16 An owner or operator of a stationary source that has more than a threshold quantity of a regulated substance in a process, as determined under 40 CFR 68.115, shall comply with the requirements of the Chemical Accident Prevention Provisions at 40 CFR 68 no later than the latest of the following dates:

Three years after the date on which a regulated substance present above a threshold quantity is first listed under 40 CFR 68.130.

The date on which a regulated substance is first present above a threshold quantity in a process.

[40 CFR 68.10 (a)]

Comment: Facility has no regulated substances on site of more than threshold quantity. 2.16 should be not applicable.

Recycling and Emissions Reductions

2.17 The permittee shall comply with applicable standards for recycling and emissions reduction pursuant to 40 CFR 82, Subpart F, Recycling and Emissions Reduction.

[40 CFR 82, Subpart F]

NSPS/NESHAP General Provisions

2.18 NSPS 40 CFR 60, Subpart A – General Provisions

The permittee shall comply with the applicable requirements of 40 CFR 60, Subpart A – General Provisions in accordance with 40 CFR 60.1. A summary of requirements for affected facilities is provided in Table 2.2.

Table 2.2 NSPS 40 CFR 60, SUBPART A – SUMMARY OF GENERAL PROVISIONS

Section	Subject	Summary of Section Requirements
60.4	Address	<ul style="list-style-type: none"> All requests, reports, applications, submittals, and other communications associated with 40 CFR 60, Subpart GG shall be submitted to: Coeur d'Alene Regional Office Department of Environmental Quality 2110 Ironwood Pkwy Coeur d'Alene, ID 83814
60.7(a),(b), and (f)	Notification and Recordkeeping	<ul style="list-style-type: none"> Notification shall be furnished of commencement of construction postmarked no later than 30 days of such date. Notification shall be furnished of initial startup postmarked within 15 days of such date. Notification shall be furnished of any physical or operational change that may increase emissions postmarked 60 days before the change is made. Records shall be maintained of the occurrence and duration of any startup, shutdown or malfunction; any malfunction of the air pollution control equipment; or any periods during which a CMS or monitoring device is inoperative. Records shall be maintained, in a permanent form suitable for inspection, of all measurements, performance testing measurements, calibration checks, adjustments and maintenance performed, and other required information. Records shall be maintained for a period of two years following the date of such measurements, maintenance, reports, and records.
60.8	Performance Tests	<ul style="list-style-type: none"> At least 30 days prior notice of any performance test shall be provided to afford the opportunity to have an observer to be present. Within 60 days of achieving the maximum production rate, but not later 180 days after initial startup, performance test(s) shall be conducted and a written report of the results of such test(s) furnished. Performance testing facilities shall be provided as follows: Sampling ports adequate for test methods applicable to such facility. Safe sampling platform(s). Safe access to sampling platform(s). Utilities for sampling and testing equipment. Performance tests shall be conducted and data reduced in accordance with 40 CFR 60.8(b), (c), and (f).
60.11(a),(c), (d), (f), and (g)	Compliance With Standards and Maintenance Requirements	<ul style="list-style-type: none"> When performance tests are required, compliance with standards is determined by methods and procedures established by 40 CFR 60.8. At all times, including periods of startup, shutdown, and malfunction, the owners and operators shall, to the extent practicable, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. For the purpose of submitting compliance certifications or establishing whether or not a person has violated or is in violation of any standard, nothing shall preclude the use, including the exclusive use, of any credible evidence or information, relevant to whether a source would have been in compliance with applicable requirements if the appropriate performance or compliance test or procedure had been performed. The opacity standards shall apply at all times except during periods of startup, shutdown, malfunction, and as otherwise provided.
60.12	Circumvention	<ul style="list-style-type: none"> No permittee shall build, erect, install, or use any article, machine, equipment or process, the use of which conceals an emission which would otherwise constitute a violation of an applicable standard.
60.14	Modification	<ul style="list-style-type: none"> A physical or operational change which results in an increase in the emission rate to the atmosphere or any pollutant to which a standard applies shall be considered a modification, and upon modification an existing facility shall become an affected facility in accordance with the requirements and exemptions in 40 CFR 60.14. Within 180 days of the completion of any physical or operational change, compliance with all applicable standards must be achieved.
60.15	Reconstruction	<ul style="list-style-type: none"> An existing facility, upon reconstruction, becomes an affected facility, irrespective of any change in emission rate in accordance with the requirements of 40 CFR 60.15.

[40 CFR 60, Subpart A]

2.19 NESHAP 40 CFR 63, Subpart A – General Provisions

The permittee shall comply with the requirements of 40 CFR 63, Subpart A – General Provisions. A summary of applicable requirements for affected sources is provided in Table 2..

Table 2.3 NESHAP 40 CFR 63, SUBPART A – SUMMARY OF GENERAL PROVISIONS

Section	Subject	Summary of Section Requirements
63.13	Addresses	<ul style="list-style-type: none"> All requests, reports, applications, submittals, and other communications associated with 40 CFR 63, Subpart(s) shall be submitted to: <div style="display: flex; justify-content: space-between;"> <div style="text-align: center;"> Director Air and Waste US EPA 1200 Sixth Avenue Seattle, WA 98101 </div> <div style="text-align: center;"> Coeur d'Alene Regional Office Department of Environmental Quality 2110 Ironwood Pkwy Coeur d'Alene, ID 83814 </div> </div>
63.4(a)	Prohibited Activities	<ul style="list-style-type: none"> No permittee must operate any affected source in violation of the requirements of 40 CFR 63 in accordance with 40 CFR 63.4(a). No permittee subject to the provisions of this part shall fail to keep records, notify, report, or revise reports as required under this part.
63.4(b)	Circumvention/ Fragmentation	<ul style="list-style-type: none"> No permittee shall build, erect, install or use any article, machine, equipment, or process to conceal an emission that would otherwise constitute noncompliance with a relevant standard. Fragmentation which divides ownership of an operation, within the same facility among various owners where there is no real change in control, will not affect applicability in accordance with 40 CFR 63.4(c).
63.6(b)	Compliance Dates	<ul style="list-style-type: none"> The permittee of any new or reconstructed source must comply with the relevant standard as specified in 40 CFR 63.6(b). The permittee of a source that has an initial startup before the effective date of a relevant standard must comply not later than the standard's effective date in accordance with 40 CFR 63.6(b)(1). The permittee of a source that has an initial startup after the effective date of a relevant standard must comply upon startup of the source in accordance with 40 CFR 63.6(b)(2). The permittee of any existing sources must comply with the relevant standard by the compliance date established in the applicable subpart or as specified in 40 CFR 63.6(c). The permittee of an area source that increases its emissions of hazardous air pollutants such that the source becomes a major source shall be subject to relevant standards for existing sources in accordance with 40 CFR 63.6(c)(5).
63.6(e)	Compliance with Standards and Maintenance Requirements (Non-Opacity)	<ul style="list-style-type: none"> At all times, including periods of startup, shutdown, and malfunction, the permittee must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions in accordance with 40 CFR 63.6(e). The permittee of an affected source must develop a written startup, shutdown, and malfunction plan and a program of corrective action for malfunctioning process, air pollution control, and monitoring equipment used to comply with the relevant standard in accordance with 40 CFR 63.6(e). The permittee must maintain the current plan at the affected source and must make the plan available upon request. If the plan fails to address or inadequately addresses a malfunction, the permittee must revise the plan within 45 days after the event. The permittee must record and report actions taken during a startup, shutdown, or malfunction in accordance with the requirements in 40 CFR 63.6(e). The permittee shall confirm that actions taken during the relevant reporting period during periods of startup, shutdown, and malfunction were consistent with the plan in the semiannual startup, shutdown, and malfunction report. Non-opacity emission standards shall apply at all times except during periods of startup, shutdown, and malfunction, and as otherwise specified, in accordance with 40 CFR 63.6(f).
63.6(h)	Compliance with Standards and Maintenance Requirements (Opacity)	<ul style="list-style-type: none"> The opacity and visible emission standards must apply at all times except during periods of startup, shutdown, and malfunction, and as otherwise specified in accordance with 40 CFR 63.6(h). The permittee shall notify in writing of the anticipated date for conducting opacity or visible emission observations in accordance with 40 CFR 63.9(f), if such observations are required, in accordance with 40 CFR 63.6(h)(4). For the purpose of demonstrating initial compliance, opacity or visible emission observations shall be conducted in accordance with 40 CFR 63.6(h)(5). The permittee shall make records available upon request and shall provide evidence indicating proof of current visible observer emission certification in accordance with 40 CFR 63.6(h)(6).
63.7	Performance Testing	<ul style="list-style-type: none"> If required to do performance testing, the permittee must perform such tests within 180 days of the compliance date in accordance with 40 CFR 63.7(a).

	Requirements	<ul style="list-style-type: none"> • The permittee must notify in writing of the intention to conduct a performance test at least 60 calendar days before the performance test is initially scheduled to begin to allow review of the site-specific test plan and to have an observer present during the test in accordance with 40 CFR 63.7(b). • Before conducting a required performance test, the permittee shall develop and, if requested, shall submit a site-specific test plan for approval in accordance with 40 CFR 63.7(c). The test plan shall include a test program summary, the test schedule, data quality objectives, and both an internal and external quality assurance (QA) program. • If required to do performance testing, the permittee shall provide performance testing facilities in accordance with 40 CFR 63.7(d): <ul style="list-style-type: none"> Sampling ports adequate for test methods applicable to such source. Safe sampling platform(s); Safe access to sampling platform(s); Utilities for sampling and testing equipment; and Any other facilities deemed necessary for safe and adequate testing of a source. • Performance tests shall be conducted and data reduced in accordance with 40 CFR 63.7(e) and (f). • The permittee shall report the results of the performance test before the close of business on the 60th day following the completion of the test, unless specified or approved otherwise in accordance with 40 CFR 63.7(g).
63.9	Notification Requirements	<ul style="list-style-type: none"> • The permittee of an affected source that has an initial startup before the effective date of a relevant standard shall notify in writing that the source is subject to the relevant standard, in accordance with 40 CFR 63.9(b)(2). The notification, which shall be submitted not later than 120 calendar days after the effective date of the relevant standard (or within 120 calendar days after the source becomes subject to the relevant standard), shall provide the following information: <ul style="list-style-type: none"> The name and address of the permittee; The address (i.e., physical location) of the affected source; An identification of the relevant standard, or other requirement, that is the basis of the notification and the source's compliance date; A brief description of the nature, size, design, and method of operation of the source and an identification of the types of emission points within the affected source subject to the relevant standard and types of hazardous air pollutants emitted; and A statement of whether the affected source is a major source or an area source. • The permittee of a new or reconstructed major affected source for which an application for approval of construction or reconstruction is required must provide the following information in writing in accordance with 40 CFR 63.9(b)(4): <ul style="list-style-type: none"> A notification of intention to construct a new major-emitting affected source, reconstruct a major-emitting affected source, or reconstruct a major source such that the source becomes a major-emitting affected source; A notification of the actual date of startup of the source delivered or postmarked within 15 calendar days after that date. • The permittee of a new or reconstructed affected source for which an application for approval of construction or reconstruction is not required must provide the following information in writing in accordance with 40 CFR 63.9(b)(5): <ul style="list-style-type: none"> A notification of intention to construct a new affected source, reconstruct an affected source, or reconstruct a source such that the source becomes an affected source, and A notification of the actual date of startup of the source delivered or postmarked within 15 calendar days after that date. <p>Unless the permittee has requested and received prior permission, the notification must include the information required in the application for approval of construction or reconstruction as specified in 40 CFR 63.5(d)(1).</p> • The permittee shall notify in writing of his or her intention to conduct a performance test at least 60 calendar days before the performance test is scheduled to begin to allow the opportunity to review and approve the site-specific test plan required by 40 CFR 63.7(c), and to have an observer present during the test. • The permittee of an affected source shall notify in writing of the anticipated date for conducting the opacity or visible emission observations in accordance with 40 CFR 63.9(f), if such observations are required. • Each time a notification of compliance status is required under this part, the permittee of such source shall submit a notification of compliance status in accordance with 40 CFR 63.9(h)(2)(i). The notification shall list: <ul style="list-style-type: none"> The methods that were used to determine compliance; The results of any performance tests, opacity or visible emission observations, continuous monitoring system

		<p>(CMS) performance evaluations, and/or other monitoring procedures or methods that were conducted;</p> <p>The methods that will be used for determining continuing compliance, including a description of monitoring and reporting requirements and test methods;</p> <p>The type and quantity of hazardous air pollutants emitted by the source (or surrogate pollutants if specified in the relevant standard), reported in units and averaging times and in accordance with the test methods specified in the relevant standard;</p> <p>If the relevant standard applies to both major and area sources, an analysis demonstrating whether the affected source is a major source (using the emissions data generated for this notification);</p> <p>A description of the air pollution control equipment (or method) for each emission point, including each control device (or method) for each hazardous air pollutant and the control efficiency (percent) for each control device (or method); and</p> <p>A statement by the permittee of the affected existing, new, or reconstructed source as to whether the source has complied with the relevant standard or other requirements.</p> <ul style="list-style-type: none"> • The notification must be sent before the close of business on the 60th day following the completion of the relevant compliance demonstration activity specified in the relevant standard unless otherwise specified in accordance with 40 CFR 63.9(h)(2)(ii). If no performance test is required but opacity or visible emission observations are required to demonstrate compliance with a standard, the notification shall be sent before close of business on the 30th day following the completion of the observations. • Each time a notification of compliance status is required under this part, the permittee of such source shall submit the notification of compliance status following completion of the relevant compliance demonstration activity specified. • If an permittee submits estimates or preliminary information in an application in place of the actual emissions data or control efficiencies, the permittee shall submit the actual emissions data and other correct information as soon as available but no later than with the initial notification of compliance status required in this section in accordance with 40 CFR 63.9(h)(5). • Any change in the information already provided under this section shall be provided in writing within 15 calendar days after the change in accordance with 40 CFR 63.9(j).
63.10	Recordkeeping and Reporting Requirements	<ul style="list-style-type: none"> • The permittee shall maintain files of all required information recorded in a form suitable and readily available for expeditious inspection and review in accordance with 40 CFR 63.10(b)(1). The files shall be retained for at least 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record. At a minimum, the most recent 2 years of data shall be retained on site. • The permittee shall maintain relevant records of the following in accordance with 40 CFR 63.10(b)(2); <ul style="list-style-type: none"> The occurrence and duration of each startup or shutdown when the startup or shutdown causes the source to exceed any applicable emission limitation in the relevant emission standards; The occurrence and duration of each malfunction of operation or the required air pollution control and monitoring equipment; All required maintenance performed on the air pollution control and monitoring equipment; Actions taken during periods of startup or shutdown when the source exceeded applicable emission limitations in a relevant standard and when the actions taken are different from the procedures specified in the affected source's startup, shutdown, and malfunction plan; or Actions taken during periods of malfunction when the actions taken are different from the procedures specified in the affected source's startup, shutdown, and malfunction plan; <p>All information necessary, including actions taken, to demonstrate conformance with the affected source's startup, shutdown, and malfunction plan (see 40 CFR 63.6(e)(3)) when all actions taken during periods of startup or shutdown (and the startup or shutdown causes the source to exceed any applicable emission limitation in the relevant emission standards), and malfunction (including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation) are consistent with the procedures specified in such plan. (The information needed to demonstrate conformance with the startup, shutdown, and malfunction plan may be recorded using a "checklist," or some other effective form of recordkeeping, in order to minimize the recordkeeping burden for conforming events);</p> <p>Each period during which a CMS is malfunctioning or inoperative (including out-of-control periods);</p> <p>All required measurements needed to demonstrate compliance with a relevant standard (including, but not limited to, 15-minute averages of CMS data, raw performance testing measurements, and raw performance evaluation measurements, that support data that the source is required to report);</p> <p>All results of performance tests, CMS performance evaluations, and opacity and visible emission observations;</p> <p>All measurements as may be necessary to determine the conditions of performance tests and performance</p>

		<p>evaluations;</p> <p>All CMS calibration checks;</p> <p>All adjustments and maintenance performed on CMS;</p> <p>All emission levels relative to the criterion for obtaining permission to use an alternative to the relative accuracy test, if the source has been granted such permission under 40 CFR 63.8(f)(6); and</p> <p>All documentation supporting initial notifications and notifications of compliance status under 40 CFR 63.9.</p> <ul style="list-style-type: none"> • If an permittee determines that his or her stationary source that emits one or more HAP, and that stationary source is in the source category regulated by the relevant standard, but that source is not subject to a relevant standard because of limitations on the source's potential to emit or an exclusion, the permittee must keep a record of the applicability determination on site at the source for a period of 5 years after the determination, or until the source changes its operations to become an affected source, whichever comes first in accordance with 40 CFR 63.10(b).
--	--	--

[40 CFR 63, Subpart A]

Incorporation of Federal Requirements by Reference

- 2.20** Unless expressly provided otherwise, any reference in this permit to any document identified in IDAPA 58.01.01.107.03 shall constitute the full incorporation into this permit of that document for the purposes of the reference, including any notes and appendices therein. Documents include, but are not limited to:
- Standards of Performance for New Stationary Sources (NSPS), 40 CFR Part 60
- National Emission Standards for Hazardous Air Pollutants for Source Categories (NESHAP), 40 CFR Part 63
- For permit conditions referencing or cited in accordance with any document incorporated by reference (including permit conditions identified as NSPS or NESHAP), should there be any conflict between the requirements of the permit condition and the requirements of the document, the requirements of the document shall govern, including any amendments to that regulation.

3. UNIT 3A - COOPER-ROLLS COBERRA 125 WITH DIFFUSION FLAME BURNER

Summary Description

Table 3.1 describes the devices used to control emissions from Unit 3A

Table 3.1 EMISSIONS UNITS AND EMISSIONS CONTROL DEVICES

PERMIT CONDITION	SOURCE DESCRIPTION	EMISSIONS CONTROL(S)
3	Unit 3a-Cooper-Rolls Coberra 125 with diffusion flame burner	NONE

Table 3.2 contains only a summary of the requirements that apply to the Unit 3A. Specific permit requirements are listed below Table 3.2.

Table 3.2 APPLICABLE REQUIREMENTS SUMMARY

Permit Conditions	Parameter	Permit Limit/ Standard Summary	Applicable Requirements Reference	Monitoring & Record-keeping Requirements
3.1	PM ^a	0.015 gr/dscf ^b at 3% O ₂ for gas	IDAPA 58.01.01.677	3.3, 3.4
3.2	Visible Emissions	20% opacity for no more than three minutes in any 60-minute period	IDAPA 58.01.01.625 PTC No. 021-00013	3.3, 3.4
3.3	Fuel	Natural gas exclusively	PTC No. 021-00013	3.4
3.5	Engine Replacement	Notify DEQ 30 days in advance	40 CFR 60.15	2.11

^aParticulate matter

^bGrains per dry standard cubic foot

Permit Limits / Standard Summary

3.1 Particulate matter emissions from Unit 3A shall not exceed the grain-loading emissions limits of 0.015 gr/dscf of effluent gas corrected to 3% O₂ by volume for natural gas.

[IDAPA 58.01.01.677, 5/1/94]

Comment: Unit 3A is not "fuel burning equipment" as defined by IDAPA 58.01.01.006.45 and not subject to this standard therefore a compliance determination is not applicable for this permit condition.

3.2 The permittee shall not discharge any air pollutant to the atmosphere from any point of emissions for a period or periods aggregating more than three minutes in any 60-minute period which is greater than 20% opacity as determined by procedures contained in the IDAPA 58.01.01.625.

[IDAPA 58.01.01.625, 3/20/98]

Operating Requirements

3.3 Unit 3A shall be fired by natural gas exclusively.

[IDAPA 58.01.01.677, 5/1/94]

Monitoring and Recordkeeping Requirements

3.4 The permittee shall monitor and record the natural gas throughput to Unit 3A monthly and annually. Throughput shall be measured in cubic feet.

[IDAPA 58.01.01.677, 5/1/94]

Reporting Requirements

- 3.5 The permittee shall notify DEQ of each engine replacement at least 30 days before the change-out, or, in emergency situations where the permittee does not know 30 days in advance, within 48 hours of the change-out. The notification shall include a statement as to whether the unit being installed has been or will be reconstructed, as defined in 40 CFR 60.15.

[40 CFR 60.15]

4. UNIT 3B-COOPER-ROLLS COBERRA 6000 WITH DRY LOW EMISSIONS COMBUSTOR

Summary Description

Table 4.1 describes the devices used to control emissions from Unit 3B.

Table 4.1 EMISSIONS UNITS AND EMISSIONS CONTROL DEVICES

SOURCE DESCRIPTION	EMISSIONS CONTROL(S)
UNIT 3B-COOPER-ROLLS COBERRA 6000 WITH DRY LOW EMISSIONS COMBUSTOR	NONE

Table 4.2 contains only a summary of the requirements that apply to the Unit 3B. Specific permit requirements are listed below Table 4.2.

Table 4.2 APPLICABLE REQUIREMENTS SUMMARY

Permit Conditions	Parameter	Permit Limit/ Standard Summary	Applicable Requirements Reference	Monitoring and Record-keeping Requirements
4.1	PM	0.015 gr/dscf @ 3% O ₂ for gas	IDAPA 58.01.01.677	4.3
4.2	Visible emissions (opacity)	20% opacity for no more than three minutes in any 60-minute period	PTC No. 021-00013	4.3
4.3	Fuel	Natural gas exclusively	PTC No. 021-00013	4.5
4.4	Throughput	2,627 MMscf/yr	PTC No. 021-00013	4.3, 4.5
4.6	NO _x emissions	42 ppmvd @ 15% O ₂	PTC No. 021-00013	4.15
4.7	NO _x emissions	197 T/yr	PTC No. 021-00013	4.8, 4.15
4.9	Fuel sulfur content	0.8% by weight	40 CFR §60.333(b) PTC No. 021-00013	4.10
4.13	NSPS	Compliance with Applicable Subparts	40 CFR 60	2.11

Permit Limits / Standard Summary

4.1 Particulate matter emissions from Unit 3B shall not exceed the grain loading emission limits of 0.015 grains per dry standard cubic foot (gr/dscf) of effluent gas corrected to 3% oxygen by volume for natural gas.

[IDAPA 58.01.01.677, 5/1/1994]

Comment: Unit 3B is not "fuel burning equipment" as defined by IDAPA 58.01.01.006.45 and not subject to this standard therefore a compliance determination is not applicable for this permit condition.

4.2 The permittee shall not discharge any air pollutant to the atmosphere from any point of emission for a period or periods aggregating more than three minutes in any 60-minute period which is greater than 20% opacity as determined by procedures contained in the IDAPA 58.01.01.625.

[IDAPA 58.01.01.625, 3/20/1998]

Operating Requirements

- 4.3 Unit 3B shall be fired by natural gas exclusively.
[PTC. No. 021-00013, 6/14/2000]
- 4.4 The maximum amount of natural gas combusted in Unit 3B shall not exceed 2,627,000,000 standard cubic feet per any consecutive 12-month period (scf/yr).
[PTC. No. 021-00013, 6/14/2000]

Monitoring and Recordkeeping Requirements

- 4.5 The permittee shall monitor and record the natural gas throughput to Unit 3B monthly and annually. Throughput shall be measured in cubic feet.
[PTC. No. 021-00013, 6/14/2000]
- 4.6 NO_x emissions from Unit 3B shall not exceed 42 ppm by volume corrected to 15% O₂. NO_x emissions shall be measured in accordance with Permit Condition 4.15.
[PTC. No. 021-00013, 6/14/2000]
- 4.7 NO_x emissions from Unit 3B shall not exceed 197 tons per any consecutive 12-month period (T/yr). NO_x emissions shall be measured in accordance with Condition 4.15.
[PTC. No. 021-00013, 6/14/2000]

- 4.8 The permittee shall monitor and record the average NO_x pound-per-hour (lb/hr) emissions rate at full-load operating conditions measured for each test required by Permit Condition 4.14. Compliance with the annual NO_x emissions rate limit shall be demonstrated as shown below.

$$(X_a \text{ lb/hr})(8,760 \text{ hr/yr})(1 \text{ T}/2000 \text{ lb}) = X \text{ T/yr}$$

Where: X_a = average pound-per-hour NO_x emissions rate at full-load operating conditions measured during testing.

[IDAPA 58.01.01.322.01, 3/19/1999]

- 4.9 No fuel containing sulfur in excess of 0.8% by weight shall be burned in Unit 3B.
[PTC. No. 021-00013, 6/14/2000]
- 4.10 In accordance with 40 CFR 60.334(h)(3)(i), the permittee shall use the gas quality characteristics in a current, valid purchase contract, tariff sheet or transportation contract for the gaseous fuel, specifying that the maximum total sulfur content of the fuel is 20.0 grains/100 scf or less.
[40 CFR 60.334(h)(3)]
- 4.11 If a replacement turbine is installed, the permittee shall conduct an initial performance test to measure oxides of nitrogen emissions in accordance with the test methods and procedures in 40 CFR 60.8, 40 CFR 60.335, IDAPA 58.01.01.157, and Permit Condition 4.15. Provided the replacement turbine demonstrates compliance with terms and conditions of this permit during the initial performance test, an additional performance test is not required during the calendar year the replacement turbine is put into service. Emissions, throughput, and rated horsepower of replacement turbines shall not exceed emission limits, throughput limits, and rated horsepower of existing Unit 3B.
[IDAPA 58.01.01.322.01, 3/19/1999]
- 4.12 The permittee shall notify DEQ of each engine replacement at least 30 days before the changeout, or in emergency situations where the permittee does not know 30 days in advance, within 48 hours of the changeout. The notification shall include a statement as to whether the unit being installed has been or will be reconstructed as defined in 40 CFR 60.15.
[40 CFR 60.335, 6/27/1989]

4.13 Stationary sources subject to 40 CFR 60 shall comply with Permit Conditions 2.19 through 2.27.
[IDAPA 58.01.01.322.02, 5/1/1994]

4.14 Unless otherwise specified by permit condition or source test plan approval, each source test shall consist of at least three test runs and the emissions results shall be reported as the arithmetic average of all valid test runs.
[40 CFR 60.8]

4.15 The permittee shall demonstrate compliance with the NO_x emission limit in Permit Condition 4.6 using EPA Method 20 in accordance with 40 CFR 60.335 as follows:

4.15.1 Testing shall be performed one time per calendar year unless the results from the first test or two subsequent tests are less than 90% of the NO_x emission limits in Permit Conditions 3.6 in which no further testing will be required on that turbine during this permit term;

4.15.2 Testing shall be performed at 30, 50, 75, and 100% of peak load or at four points in the normal operating range of the gas turbine including the minimum point in the range and peak load;

4.15.3 During each test run, the permittee shall record the following information:

- NO_x concentration (ppm by volume);
- Barometric pressure at test (mm Hg);
- Humidity of ambient air (g H₂O/g air);
- Ambient temperature (K), and
- Fuel consumption (scf/hour);

4.15.4 For each test day, the permittee shall document the higher heating value of the fuel, Btu/scf.
[40 CFR 60.335]

4.16 For all testing, the permittee shall use the following test method(s) and averaging times to measure the pollutant emissions:

Table 4.2 TEST METHODS

Pollutant	Test Method	Averaging Time	Special Conditions
NO _x ^a	EPA ^b Method 20	Rolling three-hour average for lb/hr ^c limit, 12-month rolling average for ton/year ^d limit.	Or DEQ-approved alternative in accordance with IDAPA 58.01.01.157.

^aOxides of Nitrogen

^bU.S. Environmental Protection Agency

^cPounds per hour

^dTons per year

5. NESHAP 40 CFR 63, SUBPART ZZZZ REQUIREMENTS

Summary Description

This section only applies to the emergency stationary generator.

The permittee shall comply with all applicable requirements of 40 CFR 63, Subpart ZZZZ and all applicable general provisions of 40 CFR 63 Subpart A.

Subpart ZZZZ applies to the existing stationary Reciprocating Internal Combustion Engine (RICE) located at area source of HAP emissions. Subpart ZZZZ applies to the existing emergency spark ignition with a rated capacity greater than 500 bhp. Within the context of 40 CFR 63 Subpart ZZZZ, the terms “you” and “your” mean “permittee” and “permittee’s” respectively. The following shall apply to the stationary emergency RICE:

- 5.1 In accordance with 40 CFR 63.6595(a)(1), the affected source must comply with the applicable emission and operating limitations of the National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines, 40 CFR 63, Subpart ZZZZ by October 19, 2013.

[40 CFR 63.6595(a)(1)]

Permit Limits / Standard Summary

- 5.2 In accordance with 40 CFR 63.6603(a), on and after October 19, 2013, the following emission limits or operating restrictions are required for the >500 bhp engine. The permittee must meet the following requirements, except during periods of startup.

- Change oil and filter every 500 hours of operation or annually, whichever comes first.
- Inspect spark plugs every 1,000 hours of operation or annually, whichever comes first.
- Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.

[40 CFR 63.6603(a)]

Operating Requirements

- 5.3 In accordance with 40 CFR 63.6605, on and after October 19, 2013, the permittee shall, at all times, operate and maintain the stationary emergency RICE, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require the permittee to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

[40 CFR 63.6605]

Monitoring and Recordkeeping Requirements

- 5.4 In accordance with 40 CFR 63.6625(e)(3), on and after October 19, 2013, the permittee must operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the stationary emergency RICE in a manner consistent with good air pollution control practice for minimizing emissions.

[40 CFR 63.6625(e)(3)]

- 5.5 In accordance with 40 CFR 63.6625(f), on and after October 19, 2013, an existing emergency stationary RICE located at an area source of HAP emissions must install a non-resettable hour meter if one is not already installed.

[40 CFR 63.6625(f)]

- 5.6 In accordance with 40 CFR 63.6625(h), on and after October 19, 2013, the emergency stationary RICE's time spent at idle during startup shall be minimized to a period needed for appropriate and safe loading of the stationary emergency RICE, but not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in Tables 1a, 2a, 2c, and 2d to 40 CFR 63 Subpart ZZZZ apply.

[40 CFR 63.6625(h)]

- 5.7 In accordance with 40 CFR 63.6625(j), on and after October 19, 2013, the permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in the Permit Limits/Standard Summary permit condition. The oil analysis must be performed at the same frequency specified for changing the oil. The analysis program must at a minimum analyze the following three parameters: Total Acid Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Acid Number increases by more than 3.0 milligrams of potassium hydroxide (KOH) per gram from Total Acid Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the stationary emergency RICE owner or operator is not required to change the oil. If any of the limits are exceeded, the stationary emergency RICE owner or operator must change the oil within 2 days of receiving the results of the analysis; if the stationary emergency RICE is not in operation when the results of the analysis are received, the stationary emergency RICE owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the stationary emergency RICE. The analysis program must be part of the maintenance plan for the stationary emergency RICE.

[40 CFR 63.6625(j)]

- 5.8 In accordance with 40 CFR 63.6640(f), the permittee must operate the emergency stationary RICE according to the requirements in paragraphs (f)(1)(i) through (iii). The paragraphs are as follows:

- (i) There is no time limit on the use of emergency stationary RICE in emergency situations.
- (ii) The permittee may operate the stationary emergency RICE for the purposes of maintenance checks and readiness testing, provided the tests are recommended by Federal, State or local government, the manufacturer, the vendor or the insurance company associated with the stationary emergency RICE. Maintenance checks and readiness testing of such units is limited to 100 hours per year.
- (iii) The permittee may operate the emergency stationary RICE up to 50 hours per year in non-emergency situations, but those 50 hours are counted towards the 100 hour per year provided for maintenance and testing.

[40 CFR 63.6640(f)]

- 5.9 In accordance with 40 CFR 63.6655(e), the permittee must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan if you own or operate any of the following RICE; (1) an existing stationary emergency RICE, (2) an existing stationary RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to this subpart.

In accordance with 40 CFR 63.6655(f), an existing emergency stationary RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines, you must keep records of the hours of operation of the stationary emergency RICE that is recorded through the non-resettable hour meter. The permittee must document how many hours are spent for emergency operation; including what classified the operation as emergency and how many hours are spent for non-emergency operation. If engines are used for demand response, the permittee must keep records of the notification of the emergency situation, and the time the stationary emergency RICE was operated as part of demand response.

All records shall be readily accessible in hard copy or electronic form for a minimum of five (5) years after the date of each occurrence, measurement, maintenance procedure, corrective action or report in accordance with 40 CFR 63.6660.

[40 CFR 63.6655(e,f), 63.6660]

- 5.10** Any notifications or reporting required by the National Emission Standards for Hazardous Air Pollutants: Stationary Reciprocating Internal Combustion Engines, 40 CFR 63, Subpart ZZZZ or Subpart A – General Provisions shall be submitted to the following address in accordance with 40 CFR 63.13:

Air Quality Permit Compliance
Coeur d’Alene Regional Office
Department of Environmental Quality
2110 Ironwood Parkway
Coeur d’Alene, ID 83814
Phone: (208) 769-1422
Fax: (208) 769-1404

and

EPA Region 10
Air Operating Permits, OAQ-107
1200 Sixth Ave.
Seattle, WA 98101

[40 CFR 63.13]

6. INSIGNIFICANT ACTIVITIES

Activities and emission units identified as insignificant under IDAPA 58.01.01.317.01(b) are listed in the Tier I operating permit to qualify for a permit shield.

Table 6.1 INSIGNIFICANT ACTIVITIES

Description	Emission Point	Insignificant Activities IDAPA 58.01.01.317.01 (a) (i), (b)(i) Citation
Space Heating Boilers	Point Source	58.01.01.317.01.b.i.(5)
Lubricating Oil System	Non-Point Source	58.01.01.317.07.a.i.(4)
Natural Gas Pipeline and Fuel System	Non-Point Source	58.01.01.317.01.b.i.(30)
Fugitive Emissions	Non-Point Source	58.01.01.317.01.b.i.(30)

- 6.1 There are no additional monitoring, recordkeeping, or reporting requirements for insignificant emission units or activities beyond those required in Section 2 (Facility-wide Conditions) of this operating permit.
[IDAPA 58.01.01.322.06,5/1/1994]

7. TIER I OPERATING PERMIT GENERAL PROVISIONS

General Compliance

1. The permittee shall comply with all conditions of this permit. Any permit noncompliance constitutes a violation and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or for denial of a permit renewal application.
[IDAPA 58.01.01.322.15.a, 5/1/94; 40 CFR 70.6(a)(6)(i)]
2. It shall not be a defense in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the terms and conditions of this permit.
[IDAPA 58.01.01.322.15.b, 5/1/94; 40 CFR 70.6(a)(6)(ii)]
3. Any permittee who fails to submit any relevant facts or who has submitted incorrect information in a permit application shall, upon becoming aware of such failure or incorrect submittal, promptly submit such supplementary facts or corrected information.
[IDAPA 58.01.01.315.01, 5/1/94; 40 CFR 70.5(b)]

Reopening

4. This permit may be revised, reopened, revoked and reissued, or terminated for cause. Cause for reopening exists under any of the circumstances listed in IDAPA 58.01.01.386. Proceedings to reopen and reissue a permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of the permit for which cause to reopen exists. Such reopening shall be made as expeditiously as practicable in accordance with IDAPA 58.01.01.360 through 369.
[IDAPA 58.01.01.322.15.c, 5/1/94; IDAPA 58.01.01.386, 3/19/99; 40 CFR 70.7(f)(1), (2); 40 CFR 70.6(a)(6)(iii)]
5. The filing of a request by the permittee for a permit revision, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition.
[IDAPA 58.01.01.322.15.d, 5/1/94; 40 CFR 70.6(a)(6)(iii)]

Property Rights

6. This permit does not convey any property rights of any sort, or any exclusive privilege.
[IDAPA 58.01.01.322.15.e, 5/1/94; 40 CFR 70.6(a)(6)(iv)]

Information Requests

7. The permittee shall furnish all information requested by DEQ, within a reasonable time, that DEQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit.
[Idaho Code §39-108; IDAPA 58.01.01.122, 4/5/00; IDAPA 58.01.01.322.15.f, 4/5/00; 40 CFR 70.6(a)(6)(v)]

8. Upon request, the permittee shall furnish to DEQ copies of records required to be kept by this permit. For information claimed to be confidential, the permittee may furnish such records along with a claim of confidentiality in accordance with Idaho Code §9-342A and applicable implementing regulations including IDAPA 58.01.01.128.
[IDAPA 58.01.01.322.15.g, 5/1/94; IDAPA 58.01.01.128, 4/5/00; 40 CFR 70.6(a)(6)(v)]

Severability

9. The provisions of this permit are severable, and if any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit shall not be affected thereby.
[IDAPA 58.01.01.322.15.h, 5/1/94; 40 CFR 70.6(a)(5)]

Changes Requiring Permit Revision or Notice

10. The permittee may not commence construction or modification of any stationary source, facility, major facility, or major modification without first obtaining all necessary permits to construct or an approval under IDAPA 58.01.01.213, or complying with IDAPA 58.01.01.220 through 223. The permittee shall comply with IDAPA 58.01.01.380 through 386 as applicable.
[IDAPA 58.01.01.200-223, 4/2/08; IDAPA 58.01.01.322.15.i, 3/19/99; IDAPA 58.01.01.380-386, 7/1/02; 40 CFR 70.4(b)(12), (14), (15), and 70.7(d), (e)]
11. Changes that are not addressed or prohibited by the Tier I operating permit require a Tier I operating permit revision if such changes are subject to any requirement under Title IV of the CAA, 42 U.S.C. Section 7651 through 7651c, or are modifications under Title I of the CAA, 42 U.S.C. Section 7401 through 7515. Administrative amendments (IDAPA 58.01.01.381), minor permit modifications (IDAPA 58.01.01.383), and significant permit modifications (IDAPA 58.01.01.382) require a revision to the Tier I operating permit. IDAPA 58.01.01.502(b)(10) changes are authorized in accordance with IDAPA 58.01.01.384. Off-permit changes and required notice are authorized in accordance with IDAPA 58.01.01.385.
[IDAPA 58.01.01.381-385, 7/1/02; IDAPA 58.01.01.209.05, 4/11/06; 40 CFR 70.4(b)(14) and (15)]

Federal and State Enforceability

12. Unless specifically identified as a “State-only” provision, all terms and conditions in this permit, including any terms and conditions designed to limit a source’s potential to emit, are enforceable: (i) by DEQ in accordance with state law; and (ii) by the United States or any other person in accordance with federal law.
[IDAPA 58.01.01.322.15.j, 5/1/94; 40 CFR 70.6(b)(1) and (2)]
13. Provisions specifically identified as a “State-only” provision are enforceable only in accordance with state law. “State-only” provisions are those that are not required under the Federal Clean Air Act or under any of its applicable requirements or those provisions adopted by the state prior to federal approval.
[Idaho Code §39-108; IDAPA 58.01.01.322.15.k, 3/23/98]

Inspection and Entry

14. Upon presentation of credentials, the permittee shall allow DEQ or an authorized representative of DEQ to do the following:
- Enter upon the permittee's premises where a Tier I source is located or emissions related activity is conducted, or where records are kept under conditions of this permit;
 - Have access to and copy, at reasonable times, any records that are kept under the conditions of this permit;
 - Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit; and
 - As authorized by the Idaho Environmental Protection and Health Act, sample or monitor, at reasonable times, substances or parameters for the purpose of determining or ensuring compliance with this permit or applicable requirements.

[Idaho Code §39-108; IDAPA 58.01.01.322.15.I, 5/1/94; 40 CFR 70.6(c)(2)]

New Requirements During Permit Term

15. The permittee shall comply with applicable requirements that become effective during the permit term on a timely basis.

[IDAPA 58.01.01.322.10, 4/5/00; IDAPA 58.01.01.314.10.a.ii, 5/1/94;
40 CFR 70.6(c)(3) citing 70.5(c)(8)]

Fees

16. The owner or operator of a Tier I source shall pay annual registration fees to DEQ in accordance with IDAPA 58.01.01.387 through IDAPA 58.01.01.397.

[IDAPA 58.01.01.387, 4/2/03; 40 CFR 70.6(a)(7)]

Certification

17. All documents submitted to DEQ shall be certified in accordance with IDAPA 58.01.01.123 and comply with IDAPA 58.01.01.124.

[IDAPA 58.01.01.322.15.o, 5/1/94; 40 CFR 70.6(a)(3)(iii)(A); 40 CFR 70.5(d)]

Renewal

18. a. The owner or operator of a Tier I source shall submit an application to DEQ for a renewal of this permit at least six months before, but no earlier than 18 months before, the expiration date of this operating permit. To ensure that the term of the operating permit does not expire before the permit is renewed, the owner or operator is encouraged to submit a renewal application nine months prior to the date of expiration.

[IDAPA 58.01.01.313.03, 4/5/00; 40 CFR 70.5(a)(1)(iii)]

- b. If a timely and complete application for a Tier I operating permit renewal is submitted, but DEQ fails to issue or deny the renewal permit before the end of the term of this permit, then all the terms and conditions of this permit including any permit shield that may have been granted pursuant to IDAPA 58.01.01.325 shall remain in effect until the renewal permit has been issued or denied.
[IDAPA 58.01.01.322.15.p, 5/1/94; 40 CFR 70.7(b)]

Permit Shield

- 19. Compliance with the terms and conditions of the Tier I operating permit, including those applicable to all alternative operating scenarios and trading scenarios, shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that:
 - a. Such applicable requirements are included and are specifically identified in the Tier I operating permit; or
 - i. DEQ has determined that other requirements specifically identified are not applicable and all of the criteria set forth in IDAPA 58.01.01.325.01(b) have been met.
 - b. The permit shield shall apply to permit revisions made in accordance with IDAPA 58.01.01.381.04 (administrative amendments incorporating the terms of a permit to construct), IDAPA 58.01.01.382.04 (significant modifications), and IDAPA 58.01.01.384.03 (trading under an emissions cap).
 - c. Nothing in this permit shall alter or affect the following:
 - i. Any administrative authority or judicial remedy available to prevent or terminate emergencies or imminent and substantial dangers;
 - ii. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;
 - iii. The applicable requirements of the acid rain program, consistent with 42 U.S.C. Section 7651(g)(a); and
 - iv. The ability of EPA to obtain information from a source pursuant to Section 114 of the CAA; or the ability of DEQ to obtain information from a source pursuant to Idaho Code §39-108 and IDAPA 58.01.01.122.

[Idaho Code §39-108 and 112; IDAPA 58.01.01.122, 4/5/00;
IDAPA 58.01.01.322.15.m, 325.01, 5/1/94; IDAPA 58.01.01.325.02, 3/19/99;
IDAPA 58.01.01.381.04, 382.04, 383.05, 384.03, 385.03, 3/19/99; 40 CFR 70.6(f)]

Compliance Schedule and Progress Reports

- 20.
 - a. For each applicable requirement for which the source is not in compliance, the permittee shall comply with the compliance schedule incorporated in this permit.
 - b. For each applicable requirement that will become effective during the term of this permit and that provides a detailed compliance schedule, the permittee shall comply with such requirements in accordance with the detailed schedule.
 - c. For each applicable requirement that will become effective during the term of this permit that does not contain a more detailed schedule, the permittee shall meet such requirements on a timely basis.

- d. For each applicable requirement with which the permittee is in compliance, the permittee shall continue to comply with such requirements.
[IDAPA 58.01.01.322.10, 4/5/00; IDAPA 58.01.01.314.9, 5/1/94; IDAPA 58.01.01.314.10, 4/5/00;
40 CFR 70.6(c)(3) and (4)]

Periodic Compliance Certification

21. The permittee shall submit compliance certifications during the term of the permit for each emissions unit to DEQ and the EPA as follows:
- a. The compliance certifications for all emissions units shall be submitted annually from January 1 to December 31 or more frequently if specified by the underlying applicable requirement or elsewhere in this permit by DEQ.
 - b. The initial compliance certification for each emissions unit shall address all of the terms and conditions contained in the Tier I operating permit that are applicable to such emissions unit including emissions limitations, standards, and work practices;
 - c. The compliance certification shall be in an itemized form providing the following information (provided that the identification of applicable information may cross-reference the permit or previous reports as applicable):
 - i. The identification of each term or condition of the Tier I operating permit that is the basis of the certification;
 - ii. The identification of the method(s) or other means used by the owner or operator for determining the compliance status with each term and condition during the certification period. Such methods and other means shall include, at a minimum, the methods and means required under Subsections 322.06, 322.07, and 322.08;
 - iii. The status of compliance with the terms and conditions of the Tier I operating permit for the period covered by the certification, including whether compliance during the period was continuous or intermittent. The certification shall be based on the method or means designated in Subsection 322.11.c.ii. above. The certification shall identify each deviation and take it into account in the compliance certification. The certification shall also identify as possible exceptions to compliance any periods during which compliance is required and in which an excursion or exceedance as defined under 40 CFR Part 64 occurred; and
 - iv. Such information as the Department may require to determine the compliance status of the emissions unit.
 - d. All original compliance certifications shall be submitted to DEQ and a copy of all compliance certifications shall be submitted to the EPA.
[IDAPA 58.01.01.322.11, 4/6/05; 40 CFR 70.6(c)(5)(iii) as amended,
62 Fed. Reg. 54900, 54946 (10/22/97); 40 CFR 70.6(c)(5)(iv)]

False Statements

22. No person shall knowingly make any false statement, representation, or certification in any form, notice, or report required under this permit, or any applicable rule or order in force pursuant thereto.
[IDAPA 58.01.01.125, 3/23/98]

No Tampering

23. No person shall knowingly render inaccurate any monitoring device or method required under this permit or any applicable rule or order in force pursuant thereto.
[IDAPA 58.01.01.126, 3/23/98]

Semiannual Monitoring Reports

24. In addition to all applicable reporting requirements identified in this permit, the permittee shall submit reports of any required monitoring at least every six months. The permittee's semiannual reporting periods shall be from January 1 to June 30 and July 1 to December 31. All instances of deviations from this operating permit's requirements must be clearly identified in the report. The semiannual reports shall be submitted to DEQ within 30 days of the end of the specified reporting period.
[IDAPA 58.01.01.322.15.q, 3/23/98; IDAPA 58.01.01.322.08.c, 4/5/00; 40 CFR 70.6(a)(3)(iii)]

Reporting Deviations and Excess Emissions

25. The permittee shall promptly report all deviations from permit requirements including upset conditions, their probable cause, and any corrective actions or preventive measures taken. For excess emissions, the report shall be made in accordance with IDAPA 58.01.01.130-136. For all other deviations, the report shall be made in accordance with IDAPA 58.01.01.322.08.c, unless otherwise specified in this permit.
[IDAPA 58.01.01.322.15.q, 3/23/98; IDAPA 58.01.01.135, 4/11/06; 40 CFR 70.6(a)(3)(iii)]

Permit Revision Not Required

26. No permit revision shall be required under any approved economic incentives, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in the permit.
[IDAPA 58.01.01.322.05.b, 4/5/00; 40 CFR 70.6(a)(8)]

Emergency

27. In accordance with IDAPA 58.01.01.332, an "emergency," as defined in IDAPA 58.01.01.008, constitutes an affirmative defense to an action brought for noncompliance with such technology-based emissions limitation if the conditions of IDAPA 58.01.01.332.02 are met."
[IDAPA 58.01.01.332.01, 4/5/00; 40 CFR 70.6(g)]